

## Refrigeration Equipment Reach-In Freezer, 3 Doors, 72 cu.ft - Stainless Steel

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



738246 (KCHRI81R3DF)

3-door reach-in freezer,  
stainless steel, 72 cubic feet,  
R404a refrigerant gas, -9°F

### Short Form Specification

**Item No.** \_\_\_\_\_

3 full doors freezer with exterior back and bottom panels in galvanized steel, exterior side and top panels in 430 stainless steel; interior back, side, top and bottom panels in 304 stainless steel.

Control with cabinet temperature display. Self-closing and on-site reversible door feature lock and key.

R404a gas in the refrigeration circuit.  
ETL Safety and Sanitation certifications.  
3/5 Years warranty.

### Main Features

- External temperature display.
- Removable door gasket for easy cleaning operations.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmental impact.
- Bottom mounted cooling unit slides out for easy access and cleaning.
- Interior LED light to save energy and for best internal visibility.


### Construction

- Lockable door.
- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.

### Optional Accessories

- shelf for 54" and 81" (left/right) reach-in  PNC 880591
- middle shelf for 81" reach-ins  PNC 880592
- shelf clips  PNC 880611

APPROVAL: \_\_\_\_\_



### Electric

<b>Supply voltage:</b>	
738246 (KCHRI81R3DF)	230 V/1 ph/60 Hz
<b>Electrical power, max:</b>	1 kW
<b>Current consumption:</b>	8 Amps
<b>Plug type:</b>	USA NEMA L14-20P

### Key Information:

<b>Capacity (Cu. Ft.)</b>	72
<b>Door hinges:</b>	1 Left+2 Right
<b>External dimensions, Width:</b>	81 " (2057 mm)
<b>External dimensions, Depth:</b>	32 11/16" (830 mm)
<b>External dimensions, Height:</b>	82 1/4" (2090 mm)
<b>Number and type of doors:</b>	3 Full
<b>Internal Dimensions (depth):</b>	27 1/16"
<b>Internal Dimensions (height):</b>	60 1/4"
<b>Internal Dimensions (width):</b>	76 5/16"
<b>Shipping height:</b>	84 5/8" (2150 mm)
<b>Shipping weight:</b>	776 lbs (352 kg)
<b>Shipping volume:</b>	139.55 ft <sup>3</sup> (3.95 m <sup>3</sup> )
<b>Number and type of grids (included):</b>	9 - Coated Steel
<b>Compressor Horsepower:</b>	1 1/4
<b>Type of external material:</b>	430 AISI
<b>Type of internal material:</b>	304 AISI
<b>Warranty:</b>	3 / 5 years

### Refrigeration Data

<b>Refrigerant type:</b>	R404A
<b>Refrigerant weight:</b>	0 g
<b>Operating temperature min.:</b>	-7.6 °F
<b>Operating temperature max.:</b>	-4 °F
<b>Condenser type:</b>	Fin & tube
<b>Defrost type:</b>	Auto Defrost