

COMMERCIAL

Refrigeration Equipment Undercounter Freezer, 12 cu.ft, 48 " with 2 Doors - Stainless Steel (R290)

ITEM #
MODEL #
NAME #
SIS #
AIA #



738266 (KCHUC48F)

2-door undercounter freezer, 48", R290 refrigerant gas, -9° F, stainless steel

Short Form Specification

Item No.

2-door freezer counter top with exterior back panel in aluminium, exterior bottom panel in galvanized steel, exterior side and top panel in 430 stainless steel; interior back, top and bottom panels in 304 stainless steel.

Fin & tube condenser to improve the performances in high temperature environments. Automatic Defrost Cooling System and temperature control. Vinyl heavy duty adjustable, easy to handle and clean shelves. External temperature display.

R290 gas in refrigeration circuit.

ETL Safety and Sanitation certified.

3/5 Years warranty.

Main Features

- External temperature display.
- Removable door gasket for easy cleaning operations.
- Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3) CFC and HCFC free.
- Fin & Tube Condenser improves performance in high temperature environments.
- Automatic Defrost Cooling System provides worry-free performance.
- Electronic Temperature Control, quick and simple to set, with control display for easy monitoring.
- Heavy duty Vinyl coated steel shelves.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- High efficiency components to minimize the energy consumption still guaranteeing the highest performances.
- Cabinet and door insulated with high density polyurethane for low environmetal impact.

Construction


- Self-closing door with 90-degree stay-open feature.
- Heavy duty casters.
- Pre-wired heavy duty power cord.
- Heavy duty door hinges.
- Magnetic door gasket removable without tools for easy cleaning.


Optional Accessories

•	shelf for 48" and 72" (left/right) mega top, salad and undercounter	PNC 880597 □
•	shelf clips	PNC 880611 □
•	drawers kit for 48" mega top & undercounter	PNC 880616

APPROVAL:







EI = Electrical connection RI = Refrigerant Inlet RO = Refrigerant Outlet

Electric

Supply voltage:

738266 (KCHUC48F) 115 V/1 ph/60 Hz

Electrical power, max: 0.4 kW
Current consumption: 4 Amps

Plug type: USA NEMA 5-15P

Capacity:

Gross capacity: 12 cu.feet

Key Information:

Door hinges: 1 Left+1 Right **Capacity:** 12 cu.ft.

External dimensions, Width: 48 3/16" (1225 mm)
External dimensions, Depth: 29 15/16" (760 mm)
External dimensions, Height: 35 1/2" (902 mm)
Internal Dimensions (depth): 22 13/16"
Internal Dimensions (height): 23 1/2"

Internal Dimensions (width): 42 1/2"

Shipping height: 38 3/16" (970 mm)

Shipping weight: 287 lbs (130 kg)

Shipping volume: 34.66 ft³ (0.98 m³)

Number and type of grids

(included):2 - Vinyl-Coated SteelType of external material:Stainless SteelType of internal material:PolystyreneWarranty:3 / 5 years

Refrigeration Data

Compressor Horsepower: 1/4
Refrigerant type: R290
Refrigerant weight: 100 g
Operating temperature min.: -9.4 °F
Operating temperature max.: 8.6 °F
Condenser type: Fin & tube
Defrost type: Auto Defrost







