KitchenAid COMMERCIAL

2000 North M-63, Benton Harbor, MI 49022 855-845-9684 web: www.kitchenaidcommercial.com email: commercial@kitchenaid.com

Project		
Name		
Item #		
Quantity		
Available at		
Approval		

Commercial KSBC1B2 Series

ENCLOSURE BLENDER

NSF CERTIFIED FOR COMMERCIAL USE

- QUIET OPERATION NSF Certified, lift up sound enclosure helps reduce noise while blending - ideal for commercial environments where consumers are present. Enclosure is removable, making clean up quick and easy.
- POWER FOR OPTIMAL PERFORMANCE The blender's powerful 3.0 Peak HP motor*, 60-oz BPA-free jar, and stainless steel blade deliver optimal performance and taste for every blend.
- VARIABLE TIMER CONTROL Take care of your customers while we take care of your perfect blend with the variable timer control, which ranges from 5-60 seconds. This cycle starts at a low rpm for thorough ingredient incorporation and then ramps up to a high speed.
- SIMPLE CONTROLS, LESS HASSLE Quickly and easily create all of your best blends with the simple controls high, medium and low speed options, plus pulse and variable timer control.
- SMOOTH, CONSISTENT TEXTURE Unique asymmetric blade design + motor combine to deliver the perfect blend that pulls ingredients into the vortex at four different angles for a smooth, consistent texture.
- OPTIMAL BLENDING SPEED Intelli-Speed® Motor Control senses contents and maintains optimal speed to power through all ingredients.
- THE RIGHT CAPACITY Blend small or large batches with the BPA-Free 60-oz. jar, designed and engineered to further optimize the blender's performance, leveraging the powerful motor and exclusive KitchenAid blade design. The jar's beveled corner allows for clean pouring from three sides.
- MEASURING MADE EASY Add ingredients as you blend with a built-in measuring cap.
- STABLE AND SECURE Secure-fitting lid adds extra ease of use and helps to minimize spills when blending. A removable, jar pad holds the blender jar securely to the base to increase stability.

- EASY CORD REPLACEMENT Detachable, 6' Power Cord for quick and easy replacement, without the need for a service call.
- LASTING QUALITY High-quality, die-cast metal construction of the base, dial, enclosure handle and switches are easy to clean and built to last and withstand heavy use in a commercial environment.
- EVEN BLENDING Thicker ingredients and large quantities sometimes need a little help to blend smoothly. Tamper included to push ingredients down into the blending vortex and ensure even blending.
- 2 YEAR LIMITED WARRANTY** 2 Year Limited Hassle-Free Warranty for Blender Base and Enclosure
- INCLUDES Blender base, Blender jar, Enclosure, and Tamper





MOTOR

1800 Watts 3.0 Peak HP High-Efficiency DC Motor* 120 V, 60 Hz 15.0 A Single Phase









Commercial KSBC1B2 Series ENCLOSURE BLENDER







KSBC1B2BM



KSBC60S (Sold Separately)



Accessories Available

KSBC56D



KSBC9FT (Sold Separately)

MODELS

INDIVIDUAL UNIT W/O PACKAGING

INDIVIDUAL UNIT W/GIFT PACKAGING*

MODEL#	COUNTERTOP BLENDER	UPC
KSBC1B2CU	Commercial Enclosure Blender - Contour Silver	883049 48641 3
KSBC1B2BM	Commercial Enclosure Blender - Matte Black	883049 48640 6
MODEL#	ACCESSORIES	UPC
KSBC60S	60 oz Standard Jar	883049 41043 2
KSBC56D	56 oz Thermal Control Jar	883049 41044 9
KSBC9FT	Flex Edge Tamper	883049 43220 5

PACKAGING DIMENSIONS

	Gross Weight wit	thout Packaging	Depth without Packaging		Width without Packaging		Height without Packaging		Qty
Model	lbs	kg	in	cm	in	cm	in	cm	units
KSBC1B2BM, CU	26.5	12.0	12.2	31.0	10.1	25.7	18.8	47.7	1
Accessories	Gross Weight without Packaging		Depth without Packaging		Width without Packaging		Height without Packaging		Qty
KSBC60S	2.7	1.23	5.75	14.6	5.75	14.6	10.63	27	1
KSBC56D	3.8	1.72	6.5	16.51	6.5	16.51	10.63	27	1
KSBC9FT	0.46	0.21	3	7.62	3	7.62	11.60	29.46	1

	Gross Weight w	vith Packaging	Depth with Packaging Width with Packagin		th Packaging	Height wit	Qty		
Model	lbs	kg	in	cm	in	cm	in	cm	units
KSBC1B2BM, CU	34.5	15.6	14.8	37.6	29.5	74.9	18.4	46.7	1
Accessories	Gross Weight w	vith Packaging	Depth with	Depth with Packaging Width with Packaging		Height with Packaging		Qty	
KSBC60S	3.41	1.55	9	22.86	9	22.86	12	30.48	1
KSBC56D	4.58	2.08	9	22.86	9	22.86	12	30.48	1
KSBC9FT	0.6	0.27	3.5	8.89	3.5	8.89	12	30.48	1
			ı	ı					

*also serves as overpack



