

# WORKTOP REFRIGERATOR





## Stainless steel cabinet construction

Stainless steel interior and exterior (galvanized steel back & bottom).



## Temperature range between 33°F ~ 39°F

Air guard on rear wall ensures proper air circulation and cooling.



#### Hydrocarbon refrigerants (R-290)

Increases energy HFC refrigerants. It is safer for the environment and does not cause ozone depletion.



# Visual and audible door open alarm

Alarm sounds when doors are not completely closed to protect against food spoilage





## Cabinet Dimensions (inches/mm)

L D H
27 11/16" 33" 41 27/32"
703 mm 839 mm 1063 mm

Weight (lbs/kg)

Net Weight S 150 lbs 68 kg

Ship Weight 188 lbs 85.3 kg

### Cabinet construction

- Cyclopentane Insulation Contains no hydro-fluorocarbons (HFCs) and is environmentally friendly.
- Epoxy coated wire shelves with adjustable shelving height.
- •6" back splash guard
- •2 shelves per compartment.
- Four 4" Diameter swivel casters with front brakes standard.

#### Refrigeration

- Self-contained system, rear mounted compressor.
- Electrodeposition coated evaporator increases performance by maintaining the heat transfer rates over the life of the evaporator and reducing potential corrosion.
- •Innovative hot gas frame heating system reduces condensation and increases energy.

## Design & Features

- Self-diagnostic digital temperature control & monitor system.
- · Digital display allows for easy monitoring.
- Digital controls include manual defrost for easy maintenance.
- Rounded corner design gives a stylish appearance and reduces chances of injury.


#### Doors


- Self-closing doors
- Durable door gasket with easy replacement.
- Lifetime guaranteed heavy duty all metal door handles. (Ni-Cr Plated)

## Optional Features & Accessories


- 2.5" diameter casters available.
- · Additional shelves are available.

Front view Side view





Top view



**Doors** Capacity Cu.Ft. **Shelves** 2 Refrigerant R-290 **Temperature** 33°F ~ 39°F Range Easy Sliding Condensing Unit Maintenance 9.8 ft long (3m) flexible three Connection wire cord with modeled plug HP 1/4 HP Voltage 115V/60Hz 3.6 **Amps NEMA** Config. NEMA 5-15



- This product may exprose you to chemicals including Diisononyl Phthalate(DINP), which is known to the State of California to cause cancer. For more information go to www.P65War nings.ca.gov.
- Ce produit peut vous exposer á des agents chimiques incluant le Diisononyl
   Phthalate(DiNP), reconnu par l'Esat de Californie comme causant le cancer, Pour de plus
   amples renseignements, consulter le site www.P65Wamings.ca.gov.





Blue Air has right to change specifications without further notice.





1-886-677-8500

