

U.S.A FOODSERVICE DIVISION

TRUE MANUFACTURING CO., INC.

2001 East Terra Lane • O'Fallon, Missouri 63366-4434 • (636)240-2400 Fax (636)272-2408 • Toll Free (800)325-6152 • Intl Fax# (001)636-272-7546 Parts Dept. (800)424-TRUE • Parts Dept. Fax# (636)272-9471 • www.truemfg.com Model:

TBR72-RISZ1-L-B-111-1

PROJECT NAME LOCATION ITEM # QTY AIA # MODEL # SIS

True Bar Refrigerator:

Reach-In Single Zone Refrigerator



FEATURES

- ▶ R290 Hydrocarbon refrigerant
- Temperatures of 33°F to 38°F (.5°C to 3.3°C)
- Exterior: Black powder coated cold rolled steel with stainless steel countertop
- Interior: Stainless steel
- RCU Technology
- White LED interior lighting
- NSF/ANSI standard 7 compliant for open food product
- UL Rated for outdoor use
- Three (3) interior access ports
- Field reversible doors
- Zero clearance (side and back)
- Front air intake / front air discharge
- ▶ Electronic temperature control with exterior digital display

ROUGH-IN DATA

Specifications subject to change without notice. Chart dimensions rounded up to the nearest 1/8" (millimeters rounded up to next whole number).

Cabinet Dimensions Cord Crated Capacity (inches) 115V/60/1 Length‡ Weight (mm) Voltage 12 oz. (total ft.) (lbs.) W HP NEMA Model **Doors Shelves** 12 oz. Cans **Bottles** D† **Amps** (total m) (kg) TBR72-RISZ1-L-B-111-1 3 9 125 6-pks 78 6-pks 72 24% 343/4 5-15P **TBD** 1/4 3.2 10 **TBD** 1829 631 881 3.04

† Depth does not include 1/8" (16 mm) for slide door handles. * Height does not include 1/4" (7 mm) for leg levelers.

‡ Cord length listed represents usable cord length.



Model:

TBR72-RISZ1-L-B-111-1

True Bar Refrigerator:

Reach-In Single Zone Refrigerator

TILE ®

ADDITIONAL FEATURES

REFRIGERATION SYSTEM

- Factory engineered, self-contained, capillary tube system
- Environmentally friendly R290 hydrocarbon refrigerant
- Forced air refrigeration system which maintains 33°F to 38°F (.5°C to 3.3°C) product temperatures
- Exclusive RCU technology allows for the reversing of the condensor fan motor, helping to keep the condensing coil clean and reduce the negative effects of a dirty coil

CABINET CONSTRUCTION

- Exterior: Black, powder coated cold-rolled steel with stainless steel countertop.
- Interior: Stainless steel floor and sides with ABS plastic ceiling
- Insulation: Entire cabinet is foamed-in-place using a high density, polyurethane insulation that has zero ozone depletion and zero global warming potential
- Base fitted with leg levelers

DOORS

- Low-E, double pane thermal insulated glass doors with black powder coated door frames
- Self-closing slide doors.

SHELVING

- Nine (9) adjustable, gray PVC coated wire shelves. 17% "W x 18"D (437 mm x 458 mm). Four (4) chrome plated shelf clips included per shelf.
- Aluminum shelf support pilasters. Shelves are adjustable on ½" (13 mm) increments

MODEL FEATURES

- NSF/ANSI Standard 7 compliant for open food
- UL approved for outdoor use
- Electronic temp control with exterior digital display
- Three (3) access ports standard (see drawing for locations)

ELECTRICAL


 Unit completely pre-wired at factory and ready for final connection to a 115/60/1 phase, 15 amp dedicated outlet. Cord and plug set included.




OPTIONAL FEATURES/ACCESSORIES Upcharge and lead times may apply.


- ☐ TruLumina® 14-Color LED lighting
- ☐ Castors: ½ " (23 mm) rollers, 2" (51mm), 3" (77mm), 4" (102mm), 5" (127mm) castors ☐ 6" (153mm) legs
- G ("(153......) --i---i-l
- ☐ 6" (153mm) seismic legs
- □ Rachet locks
- ☐ Alternative temperature zones available (contact factory)

PLAN VIEW






FRONT VIEW



TOP VIEW



BACK VIEW

SIDE VIEW

PLAN VIEW NOTES

- Dimensions in brackets are in millimeters.
- Depth does not include % " (16 mm) for door handles.
- Height does not include ¼ " (7 mm) for leg levelers

YEAR
PARTS + LABOR COMPRESSOR

WARRANTY
(U.S.A. only)

SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE
METRIC DIMENSIONS ROUNDED UP TO THE NEAREST WHOLE MILLIMETER

TRUE MANUFACTURING CO., INC.