

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

Project:			
Model #:			
Item #:			
Available W/H:		Qty:	
Approval:			
AIA#:	SIS#:		
CSI Section 11400			

Worktop Freezer

Worktops PRO Series

Model: PWF-60-N

Patented Self-Cleaning Condenser



This product is equipped with a fine mesh filter to the front of the condenser to catch dust, and a rotating brush that moves up and down daily to remove excess buildup outward and away.



≡ FEATURES & BENEFITS ==

■ Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing

■ Digital temperature control & monitor system Keeps food products safe by maintaining constant temperatures.

External digital display allows for easy monitoring.

■ Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Stainless steel cabinet construction

The PRO series model boasts a stainless steel interior (Aluminum door liner) and a 22 gauge stainless steel exterior (galvanized steel bottom). It guarantees the utmost in cleanliness and long product life. The PRO series adds a touch of style to the most refined setting.

Sturdy, clean stainless steel shelving

Shelves are the most important part of cleanliness as they come in direct contact with food. Only the PRO series uniquely provides stainless steel shelving.

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

■ High-density polyurethane insulation

The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

- Spring assisted heavy duty gravity hinge
- Freezer holds -10°F ~ 0°F for the best in frozen food preservation
- Lifetime guaranteed heavy duty hinges and handles
- Built to maintain NSF standard temperatures in 100°F ambient











Model	Swing Doors	CU./FT.	#of Shelves	HP	AMPS	Crated Weight (lbs.)	L x D*x H [†] (inches)
PWF-60-N	2	17.2	2	1/2	8	349	601/4 x 30 x 335/8

(unit: inch)

Model: PWF-60-N

ELECTRICAL DATA				
Voltage	115/60/1			
Plug Type	(i) NEMA 5-15P			
Full Load Amperes	8			
Compressor HP	1/2			
Cord Length (ft.)	10			
Refrigerant	R-290			
DIMENSIONAL DATA				
Net Capacity (cu. ft.)	17.2			
Ext. Length Overall (in.)	601/4 (1530mm)			
Ext. Depth Overall (in.)*	30 (762mm)			
Ext. Height Overall (in.)†	335/8 (853mm)			
# of Doors	2			
# of Shelves	2			
Shelf Size (L x D) (in.)	27 x 17			
Net Weight (lbs.)	258			
Gross Weight (lbs.)	349			

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection.

5 Year Parts and Labor Warranty WARRANTY: 7 Year Compressor Warranty


STANDARD FEATURES


- Anti-corrosion coated evaporator
- · Self-contained system
- · 4" dia. swivel casters with locks on the front set
- Door locks
- ** Lead time applies. Please contact your sales representative for more details to order.

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, 1/2" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600
- Double overshelf, 18/304 stainless steel, 60-1/4" W: TSOS-5R

PLAN VIEW





SIDE VIEW

Ver.20221230













■ **Turbo Air**: 800-627-0032 ■ **GK**: 800-500-3519













^{*} Depth does not include 2" for door handle & rear spacers.

[†] Height does not include 5" for caster height.