

Project:	AIA#
ltem:	
Location:	SIS#
Approved:	

HORIZON TOP MOUNT REACH-IN

MODEL: HR2HC-1S

HR2HC Double Doors Reach-in Refrigerator **Hydrocarbon Series**



3 Year Parts/Labor Warranty Additional 4 Year Compressor Warranty

CABINET CONSTRUCTION

- Exterior is stainless steel front and gray painted sides
- Interior liner is made of corrosion resistant aluminum
- Full electronic control
- One piece grille
- LED interior light
- Self-closing door with 120° stay-open feature, on cam-lift hinges
- Field reversible doors
- Door locks
- Snap-In magnetic gaskets for positive door seal
- Heavy-duty epoxy coated wire shelves
- 6" Heavy-duty casters, two (2) with brakes
- 8' Cord and plug (see electrical data for details)

OPTIONS & ACCESSORIES

- Tray slide pair, 1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (A)
- Stainless steel universal tray slide pair,1 tray slide set for (1) 18" x 26" or (2) 14" x 18" pans (AC)
- Tray slide kit #4 (19 sets per half section)
- Additional shelves
- · Shelf clips
- Stainless steel breaker
- 6" Legs seismic/flanged
- 3" Casters
- Remote option* (see note on back page)

FINISH OPTION

HR Standard

(S/S front, continuous coil coated sides, aluminum interior)

(S/S front, S/S sides, aluminum interior)

HRS

(S/S front, continuous coil coated sides, S/S interior)

(Complete S/S exterior & interior)

REFRIGERATION SYSTEM

- Uses environmentally friendly, energy efficient R290 refrigerant, and meets all regulatory requirements for CARB, SNAP, DOE &
- · Hot gas condensate evaporator
- Adaptive defrost
- · Epoxy coated evaporator coil
- Maintains product temperatures between 36°F and 38°F
















MODEL	HR2HC-1S	
EXTERNAL DIMENSIONAL DATA		
Width Overall	52"	
Depth Overall with Handle	33 1/8"	
Height Overall with Casters	85"	
Number of Doors	2	
Depth with Door Open 90°	55 ½"	
Door Opening (in)	21 %" x 61 %"	
INTERNAL DIMENSIONAL DATA		
NET Capacity (cubic ft.)	45.2	
Internal Width Overall (in)	48″	
Internal Depth Overall (in)	25 %"	
Internal Height Overall (in)	62"	
Number of Shelves	6	
ELECTRICAL DATA		
Full Load Amperes 115/60/1	6.0	
REFRIGERATION DATA		
Capacity (BTU/Hr)*	Variable Speed Technology	
SHIPPING DATA		
Gross Weight (crated lbs)	540 lbs	
Height - Crated	88"	
Width - Crated	55"	
Depth - Crated	36"	

*NOTE: Remote units are field wired and come with 6" legs. Refrigerant must be specified at time of order.

Top Mount Reach-In Refrigerator Model: HR2HC-1S



*ELECTRICAL CONNECTION



Unit pre-wired at factory and include 8' long cord and plug set.













