

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project: | | |
|-------------------|--------|------|
| Model #: | | |
| Item #: | | |
| Available W/H: | | Qty: |
| Approval: | | |
| AIA#: | SIS #: | |
| CSI Section 11400 | | |
| | | |

Sandwich / Salad Unit

Food Prep Tables **J** Series

Model : JST-60-N



🚐 FEATURES & BENEFITS 💳

Digital temperature control & monitor system Keeps food products safe by maintaining constant temperatures. External digital display allows for easy monitoring.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Exterior & interior of the cabinet

The Turbo Air J series boasts a stainless steel exterior (galvanized steel back and bottom). Interior is stainless steel floor with AL sides, back and AL door liners. It guarantees the utmost in cleanliness and long product life. The J series adds a touch of style to the most refined setting.

Side mount compressor unit

With compressors positioned on the side of the unit, our refrigerators can now be serviced without being moved. Our front air intake feature also allows this model to be highly efficient in narrow spaces.

High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.

Ergonomically designed doors

Customers' fatigue fades away with easy grip handles and doors that open effortlessly. These features along with self-closing doors make this the ultimate choice in customer convenience.

- Magnetic door gaskets Magnetic door gaskets are of one-piece construction, removable without tools for ease of cleaning and replacement.
- Easy open front grille with condenser cleaning brush kit

Front grille cover is easily removable without any tools, which makes condenser cleaning easy and convenient at any time. Handy condenser cleaning brush is included inside the front grille cover.

9-1/2" deep, 1/2" thick high-density Polyethylene cutting board included with convenient side rail

LED interior lighting & fan control

Energy efficient LED lighting lights every corner, making items easy to find. Fan control function automatically shuts off the fan when the door is open, which prevents hot air from being drawn in, thus maintaining the cool inner temperature.

- Adjustable, heavy duty, PE (polyethylene) coated wire shelves
- Refrigerator holds 33°F ~ 39°F for the best in food preservation

| Model | Swing Doors | CU./FT. | #of Shelves | #of Pans | #of Hood | HP | AMPS | Crated Weight (lbs.) | $L \ge D^* \ge H^{\dagger}$ |
|----------|----------------|---------|----------------|-------------|-------------|-----|------|-------------------------|-----------------------------|
| JST-60-N | 2 | 15 | 2 | 14 | 1 | 2/5 | 3.5 | 231 | 59 x 271/2 x 353/4 |

Ver.20220719 Printed in U.S.A.

* Depth does not include 1-1/2" for cutting boards and 1" for rear spacers. † Height does not include 5" for caster height.

Sandwich / Salad Unit

Model : JST-60-N

| ELECTRICAL DATA | | | | |
|----------------------------|-------------------------------|--|--|--|
| Voltage | 115/60/1 | | | |
| Plug Type | (i) NEMA 5-15P | | | |
| Full Load Amperes | 3.5 | | | |
| Compressor HP | 2/5 | | | |
| Cord Length (ft.) | 9 | | | |
| Refrigerant | R-290 | | | |
| DIMENSIONAL DATA | | | | |
| Ext. Length Overall (in.) | 59 (1500mm) | | | |
| Ext. Depth Overall (in.)* | 271/2 (700mm) | | | |
| Ext. Height Overall (in.)† | 353/4 (909mm) | | | |
| # of Doors | 2 | | | |
| # of Shelves | 2 | | | |
| # of Pans | 14 | | | |
| Net Capacity (cu. ft.) | 15 | | | |
| Shelf Size (L x D) (in.) | 21 1/2 x 17 3/4 | | | |
| Net Weight (lbs.) | 213 | | | |
| Gross Weight (lbs.) | 231 | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1-1/2" for cutting boards and 1" for rear spacers.

+ Height does not include 5" for caster height.

WARRANTY : 2 Year Parts and Labor Warranty Additional 3 Year Warranty on Compressor

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters with locks on the front set
- 1/6 size, 4" deep condiment pans included

OPTIONAL ACCESSORIES

- 1" caster, 1/2" diameter & 13 TPI: S28R813660 (non-brake)
- 2.5" caster, ½" diameter & 13 TPI: 30265H0100 (non-brake), 30265H0200 (w/ brake)
- 5" caster, ½" diameter & 13 TPI: M726500100 (non-brake), M726500200 (w/ brake)
- Leveling leg, 1/2" 13 TPI x 1.54": LFM1213566
- 6" ABS plastic leg: 30221M0200
- 6" stainless steel leg: 30221M0600

lurbo air

- Additional PE coated wire shelf: BR99000102
- Door lock: extra lead time will apply, please call factory for more details to order

(GERMAN


KNIFE


Ver.20220719




PLAN VIEW

(unit : inch)





TOP VIEW



SIDE VIEW

Turbo Air : 800-627-0032 **GK** : 800-500-3519

■ Warranty : 800-381-7770 ■ AC : 888-900-1002

Texaking

Continued product development may necessitate specification changes without notice.

Turbo air