

Project Name:	
Location:	
Item #:	Qty:
Model:	

30" MODULAR ICE MACHINES

MODEL:

MIM452





Designed to fit with the Maxx Ice MIB400 and MIB580 Bins (sold separately)

ELECTRIC -

120V / 60Hz / 1Ph International voltage available 6' (2m) NEMA 5-15P cord set included



NEMA 5-15P

3RD PARTY APPROVALS











DOE 2018 Compliant

Meets Energy Star Guidelines

MAXX ICE WARRANTY (USA / CANADA) -

Contact Maxx Ice for warranty statement at TechnicalServices@TheLegacyCompanies.com or 877.368.2797

Maxx Ice modular, air-cooled ice machines are designed for high volume ice production application. The modular units are compatible with most ice storage bins and beverage dispensers. Available in both full or half dice cubes, these units feature a stainless steel exterior for easy cleaning and superior durability. The vertical evaporator and proven ice making technology will deliver years of reliable ice production.

FEATURES AND CONSTRUCTION —

- Stainless steel exterior
- Air-cooled compressor
- Automatic cleaning cycle
- Units are stackable for increased ice production (optional adapter is required)

DAILY ICE PRODUCTION ——

Air Temp 70°F (21°C) / Water Temp 50°F (10°C) MIM452......460 lbs (209 kg)

Air Temp 90°F (32°C) / Water Temp 70°F (21°C) MIM452......368 lbs (164 kg)

OPERATING REQUIREMENTS -

Ambient Air Temperature Range..... 50° to 100°F (10° to 38°C)
Water Temperature Range...... 41° to 90°F (5° to 32°C)
Water Usage per 100 lbs of ice...... 16 Gallons (60.6L)
Water Supply Line Connection....... 3/8" FPT

Water Pressure Range:


*Above 80 PSI requires a regulator Energy Consumption per 100 lbs of ice:

MIM452......7.1 kWh/100 lbs







TOP VIEW 30" (762 mm) Drop Zone 20.875" x 6.625" 530 mm x 168 mm REAR VIEW



SIDE VIEW







MODEL	EXTERNAL Dimensions	DAILY ICE PRODUCTION (70°F Air / 50°F Water)	COMPATIBLE MAXX ICE Storage bins	NET WEIGHT / Shipping Weight	AMP DRAW (Making / Harvesting)	REFRIGERANT And Charge Size	ELECTRICAL
MIM452	30" x 24" x 21" (762 x 610 x 533 mm)	460 lbs (209 kg)	MIB400 / MIB580	130 lbs (59 kg) 148 lbs (67 kg)	12.4A / 15.3A	R-404a 24.5 oz (695 g)	115V / 60Hz / 1Ph

INSTALLATION -

- A clearance of 2" from the wall is recommended to promote adequate cooling air circulation
- A gravity drain line is required to install this ice machine
- For optimal performance, the use of a water filter is recommended