



MAXX COLD

ICONIC BRANDS, LEADING INNOVATION

Bottle Coolers
Back Bar Coolers
Beer Tower Dispensers



010521



www.maxx-cold.com

3355 Enterprise Avenue • Suite 160 | Fort Lauderdale, FL 33331
Tel: 954.202.7419 | Fax: 954.202.7337 | www.maxx-cold.com

A DIVISION OF
THE LEGACY COMPANIES 



MXCR50BHC
49.4"W x 27"D x 35"H



MXCR65BHC
64.3"W x 27"D x 35"H



MXCR96BHC
95.3"W x 27"D x 35"H

Models:

MXCR50BHC - Bottle cooler; black painted steel and stainless steel exterior

MXCR65BHC - Bottle cooler; black painted steel and stainless steel exterior

MXCR96BHC - Bottle cooler; black painted steel and stainless steel exterior

All Models Feature:

- Reinforced heavy-duty crossbar can support heavy loads without breaking
- External built-in bottle opener and bottle cap catcher
- Rear stainless steel top with marine edge for storing glasses, garnishes/condiments, etc.
- Supplied with two (2) or three (3) sliding lids for easy access
- Rounded internal edges for easy cleaning
- LED lighting: Bright, long lasting and energy efficient
- Forced air cooling for high efficiency, rapid product cooling and reliable, consistent temperature control
- Uses an environmentally friendly, high r-value, efficient foam insulation to provide years of reliable, cost effective operation
- Designed with sturdy 1" rollers



MODEL	EXTERIOR DIMENSIONS	NET CAPACITY	CAN / BOTTLE CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS / DIVIDERS	ELECTRICAL
MXCR50HC	49.4" x 27" x 35" (1255 x 686 x 889 mm)	14 Cu Ft (396 L)	504 Cans 336 Bottles	33°F to 41°F (1°C to 5°C)	3A	205 lb 93 kg	R-600a 2.47 oz (70 g)	2 / 2	115V / 60Hz / 1Ph
MXCR65HC	64.3" x 27" x 35" (1633 x 686 x 889 mm)	17 Cu Ft (481 L)	768 Cans 504 Bottles	33°F to 41°F (1°C to 5°C)	3A	280 lb 128 kg	R-600a 3.17 oz (90 g)	2 / 2	115V / 60Hz / 1Ph
MXCR96HC	95.3" x 27" x 35" (2296 x 686 x 889 mm)	26 Cu Ft (736 L)	1250 Cans 824 Bottles	33°F to 41°F (1°C to 5°C)	3.3A	500 lb 227 kg	R-290a 3.53 oz (100 g)	3 / 3	115V / 60Hz / 1Ph

BACK BAR COOLERS - SOLID DOOR



MXBB60HC
23.3"W x 29.9"D x 51.7"H



MXBB70HC
47.5"W x 24.4"D x 56"H



MXBB90HC
61.06"W x 24.4"D x 56"H

Models:

MXBB60HC - Back bar cooler; black coated steel exterior

MXBB70HC - Back bar cooler; black coated steel exterior

MXBB90HC - Back bar cooler; black coated steel exterior

All Models Feature:

- Constructed of powder-coated steel exterior (black) and stainless steel interior & countertop
- Locking doors with easy to grip recessed door handles
- Supplied with four (4) 5" swivel casters (two with brakes) and can be placed on stationary leveling legs
- Equipped with four (4) or six (6) heavy-duty PVC-coated wire shelves
- Solid state digital control system
- LED temperature display
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERIOR DIMENSIONS	NET CAPACITY	CAN / BOTTLE CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXBB60HC	58.7" x 27.6" x 42.5" (1492 x 702 x 1080 mm)	13.8 Cu Ft (390 L)	528 Cans 240 Bottles	33°F to 41°F (1°C to 5°C)	3A	302 lb 137 kg	R-290a 3.88 oz (110 g)	2 Solid Doors 4 Shelves	115V / 60Hz / 1Ph
MXBB70HC	69.2" x 27.6" x 42.5" (1753 x 702 x 1080 mm)	14.5 Cu Ft (410 L)	775 Cans 352 Bottles	33°F to 41°F (1°C to 5°C)	3A	412 lb 187 kg	R-290a 3.88 oz (110 g)	2 Solid Doors 4 Shelves	115V / 60Hz / 1Ph
MXBB90HC	90.4" x 27.6" x 42.5" (2296 x 702 x 1080 mm)	25.3 Cu Ft (716 L)	1254 Cans 570 Bottles	33°F to 41°F (1°C to 5°C)	3A	408 lb 185 kg	R-290a 4.59 oz (130 g)	3 Solid Doors 6 Shelves	115V / 60Hz / 1Ph



MXBB60GHC
47.5"W x 24.4"D x 56"H



MXBB70GHC
61.06"W x 24.4"D x 56"H



MXBB90GHC
61.06"W x 24.4"D x 56"H

Models:

MXBB60GHC - Glass door back bar cooler; black coated steel exterior

MXBB70GHC - Glass door back bar cooler; black coated steel exterior

MXBB90GHC - Glass door back bar cooler; black coated steel exterior

All Models Feature:

- Constructed of powder-coated steel exterior (black) and stainless steel interior & countertop
- Locking doors with easy to grip recessed door handles
- Supplied with four (4) 5" swivel casters (two with brakes) and can be placed on stationary leveling legs
- Equipped with four (4) or six (6) heavy-duty PVC-coated wire shelves
- Solid state digital control system
- LED temperature display
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERIOR DIMENSIONS	NET CAPACITY	CAN / BOTTLE CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXBB60GHC	58.7" x 27.6" x 42.5" (1492 x 702 x 1080 mm)	13.8 Cu Ft (390 L)	528 Cans 240 Bottles	33°F to 41°F (1°C to 5°C)	3A	355 lb 161 kg	R-290a 3.88 oz (110 g)	2 Glass Doors 4 Shelves	115V / 60Hz / 1Ph
MXBB70GHC	69.2" x 27.6" x 42.5" (1753 x 702 x 1080 mm)	14.5 Cu Ft (410 L)	775 Cans 352 Bottles	33°F to 41°F (1°C to 5°C)	3A	331 lb 150 kg	R-290a 3.88 oz (110 g)	2 Glass Doors 4 Shelves	115V / 60Hz / 1Ph
MXBB90GHC	90.4" x 27.6" x 42.5" (2296 x 702 x 1080 mm)	25.3 Cu Ft (716 L)	1254 Cans 570 Bottles	33°F to 41°F (1°C to 5°C)	3A	474 lb 215 kg	R-290a 4.59 oz (130 g)	3 Glass Doors 6 Shelves	115V / 60Hz / 1Ph

BEER TOWER DISPENSERS - SINGLE TOWER



MXBD24-1BHC
23.3"W x 29.9"D x 51.7"H



MXBD48-1BHC
47.5"W x 24.4"D x 56"H



MXBD60-1BHC
61.06"W x 24.4"D x 56"H

Models:

MXBD24-1BHC - Beer tower dispenser; black coated steel exterior

MXBD48-1BHC - Beer tower dispenser; black coated steel exterior

MXBD60-1BHC - Beer tower dispenser; black coated steel exterior

All Models Feature:

- Constructed of powder-coated steel exterior (black) and interior (white)
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / TOWERS / TAP FAUCETS	ELECTRICAL
MXBD24-1BHC	23.3" x 29.9" x 51.65" (592 x 760 x 1312 mm)	7.2 Cu Ft (204 L)	33°F to 41°F (1°C to 5°C)	2.2A	161 lbs (73 kg)	R-600a 2.82 oz (80 g)	1 / 1 / 1	115V / 60Hz / 1Ph
MXBD48-1BHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	264 lbs (120 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph
MXBD60-1BHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	302 lbs (137 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph



MXBD48-2BHC
47.5"W x 24.4"D x 56"H



MXBD60-2BHC
61.06"W x 24.4"D x 56"H



MXBD72-2BHC
61.06"W x 24.4"D x 56"H

Models:

MXBD48-2BHC - Beer tower dispenser; black coated steel exterior

MXBD60-2BHC - Beer tower dispenser; black coated steel exterior

MXBD72-2BHC - Beer tower dispenser; black coated steel exterior

All Models Feature:

- Constructed of powder-coated steel exterior (black) and interior (white)
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) or six (6) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / TOWERS / TAP FAUCETS	ELECTRICAL
MXBD48-2BHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	267 lbs (121 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD60-2BHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	304 lbs (138 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD72-2BHC	73.07" x 24.4" x 56" (1856 x 620 x 1422 mm)	17.3 Cu Ft (490 L)	33°F to 41°F (1°C to 5°C)	3.0A	351 lbs (159 kg)	R-290a 4.59 oz (130 g)	3 / 2 / 4	115V / 60Hz / 1Ph

STAINLESS STEEL BEER TOWER DISPENSERS - SINGLE TOWER



MXBD24-1SHC
23.3"W x 29.9"D x 51.7"H



MXBD48-1SHC
47.5"W x 24.4"D x 56"H



MXBD60-1SHC
61.06"W x 24.4"D x 56"H

Models:

MXBD24-1SHC - Beer tower dispenser; stainless steel exterior

MXBD48-1SHC - Beer tower dispenser; stainless steel exterior

MXBD60-1SHC - Beer tower dispenser; stainless steel exterior

All Models Feature:

- Constructed of stainless steel exterior and white powder-coated interior
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / TOWERS / TAP FAUCETS	ELECTRICAL
MXBD24-1SHC	23.3" x 29.9" x 51.65" (592 x 760 x 1312 mm)	7.2 Cu Ft (204 L)	33°F to 41°F (1°C to 5°C)	2.2A	161 lbs (73 kg)	R-600a 2.82 oz (80 g)	1 / 1 / 1	115V / 60Hz / 1Ph
MXBD48-1SHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	264 lbs (120 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph
MXBD60-1SHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	302 lbs (137 kg)	R-290a 3.88 oz (110 g)	2 / 1 / 2	115V / 60Hz / 1Ph



MXBD48-2SHC
47.5"W x 24.4"D x 56"H



MXBD60-2SHC
61.06"W x 24.4"D x 56"H



MXBD72-2SHC
61.06"W x 24.4"D x 56"H

Models:

MXBD24-2SHC - Beer tower dispenser; stainless steel exterior

MXBD48-2SHC - Beer tower dispenser; stainless steel exterior

MXBD60-2SHC - Beer tower dispenser; stainless steel exterior

All Models Feature:

- Constructed of stainless steel exterior and white powder-coated interior
- Stainless steel interior floor plate
- 3" (77mm) diameter stainless steel insulated beer towers
- Locking door(s) with easy to grip recessed door handles
- Supplied with four (4) or six (6) swivel casters (two with brakes)
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Front-breathing refrigeration system



MODEL	EXTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / TOWERS / TAP FAUCETS	ELECTRICAL
MXBD48-2SHC	47.5" x 24.4" x 56" (1205 x 620 x 1422 mm)	10.5 Cu Ft (297 L)	33°F to 41°F (1°C to 5°C)	3.0A	267 lbs (121 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD60-2SHC	61.06" x 24.4" x 56" (1247 x 620 x 1422 mm)	14.2 Cu Ft (402 L)	33°F to 41°F (1°C to 5°C)	3.0A	304 lbs (138 kg)	R-290a 3.88 oz (110 g)	2 / 2 / 2	115V / 60Hz / 1Ph
MXBD72-2SHC	73.07" x 24.4" x 56" (1856 x 620 x 1422 mm)	17.3 Cu Ft (490 L)	33°F to 41°F (1°C to 5°C)	3.0A	351 lbs (159 kg)	R-290a 4.59 oz (130 g)	3 / 2 / 4	115V / 60Hz / 1Ph