



MAXX COLD

ICONIC BRANDS, LEADING INNOVATION

**Solid-Top
Chest Freezers**



010521



www.maxx-cold.com

3355 Enterprise Avenue • Suite 160 | Fort Lauderdale, FL 33331
Tel: 954.202.7419 | Fax: 954.202.7337 | www.maxx-cold.com

A DIVISION OF
THE LEGACY COMPANIES 



MXSH3.4SHC
22.8"W x 22"D x 33.625"H



MXSH5.2SHC
30.4"W x 22"D x 33.625"H



MXSH7.0SHC
37.8"W x 22"D x 33.625"H

Models:

MXSH3.4SHC - Solid-top chest freezer; coated steel exterior

MXSH5.2SHC - Solid-top chest freezer; coated steel exterior

MXSH7.0SHC - Solid-top chest freezer; coated steel exterior

All Models Feature:

- Sturdy hinged top opening lid that opens up to 90°
- Includes lock to provide security even if unattended
- Utilizes R-600A refrigerant
- Equipped with one (1) white wire storage basket
- Supplied with low profile roller wheels
- Can hold the contents safely for 2 days in case of a power outage



MODEL	EXTERNAL DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS/ BASKETS	ELECTRICAL
MXSH3.4SHC	22.8 x 22 x 33.625 579 x 559 x 854 mm	3.4 Cu Ft (96 L)	-11.2°F to -1°F (-24°C to -18°C)	1.0A	75 lbs (34 kg)	R-600a 1.76 oz (50 g)	1 / 1	115V / 60Hz / 1Ph
MXSH5.2SHC	30.4 x 22 x 33.625 772 x 559 x 854 mm	5.2 Cu Ft (147 L)	-11.2°F to -1°F (-24°C to -18°C)	1.0A	92.6 lbs (42 kg)	R-600a 1.98 oz (56 g)	1 / 1	115V / 60Hz / 1Ph
MXSH7.0SHC	37.8 x 22 x 33.625 960 x 559 x 854 mm	7.0 Cu Ft (198 L)	-11.2°F to -1°F (-24°C to -18°C)	5.6A	99.2 lbs (45 kg)	R-600a 1.90 oz (54 g)	1 / 1	115V / 60Hz / 1Ph

SOLID-TOP CHEST FREEZERS



MXSH9.6SHC
40.6"W x 29.7"D x 33.625"H



MXSH12.7SHC
50"W x 29.7"D x 33.625"H



MXSH15.9SHC
60.2"W x 29.7"D x 33.625"H

Models:

MXSH9.6SHC - Solid-top chest freezer; coated steel exterior

MXSH12.7SHC - Solid-top chest freezer; coated steel exterior

MXSH15.9SHC - Solid-top chest freezer; coated steel exterior

All Models Feature:

- Sturdy hinged top opening lid that opens up to 90°
- Includes lock to provide security even if unattended
- Utilizes R-134A refrigerant
- MXSH9.6S, MXSH12.7S: Supplied with one (1) white wire storage basket
- MXSH15.9S: Equipped with two (2) white wire storage baskets
- Supplied with low profile roller wheels
- Can hold the contents safely for 2 days in case of a power outage



MODEL	EXTERNAL DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS/ BASKETS	ELECTRICAL
MXSH9.6SHC	40.6" x 29.7" x 33.625" 1030 x 755 x 854 mm	9.6 Cu Ft (272 L)	-11.2°F to -1°F (-24°C to -18°C)	1.5A	136.7 lbs (62 kg)	R-600a 2.65 oz (75 g)	1 / 1	115V / 60Hz / 1Ph
MXSH12.7SHC	50" x 29.7" x 33.625" 1270 x 755 x 854 mm	12.7 Cu Ft (360 L)	-11.2°F to -1°F (-24°C to -18°C)	1.5A	152.1 lbs (69 kg)	R-600a 3.0 oz (85 g)	1 / 1	115V / 60Hz / 1Ph
MXSH15.9SHC	60.2" x 29.7" x 33.625" 1530 x 755 x 854 mm	15.9 Cu Ft (450 L)	-11.2°F to -1°F (-24°C to -18°C)	2.6A	185.2 lbs (84 kg)	R-290a 3.2 oz (91 g)	1 / 2	115V / 60Hz / 1Ph



MXSH19.4SHC
71.3"W x 29.7"D x 33.625"H



MXSH23.6SHC
78.75"W x 29.7"D x 33.625"H



MXSH30.0SHC
76"W x 35.25"D x 35.83"H

Models:

MXSH19.4SHC - Solid-top chest freezer; coated steel exterior

MXSH23.6SHC - Solid-top chest freezer; coated steel exterior

MXSH30.0SHC - Solid-top chest freezer; coated steel exterior

All Models Feature:

- Sturdy hinged top opening lid(s) that opens up to 90°
- Includes lock to provide security even if unattended
- Supplied with two (2) white wire storage baskets
- Equipped with low profile roller wheels
- Can hold the contents safely for 2 days in case of a power outage



MODEL	EXTERNAL DIMENSIONS	CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	LIDS/BASKETS	ELECTRICAL
MXSH19.4SHC	71.3 x 29.7 x 33.625 1810 x 755 x 854 mm	19.4 Cu Ft (549 L)	-11.2°F to -1°F (-24°C to -18°C)	2.6A	205 lbs (93 kg)	R-290a 3.53 oz (100 g)	1 / 2	115V / 60Hz / 1Ph
MXSH23.6SHC	78.75 x 29.7 x 33.625 2000 x 755 x 854 mm	23.6 Cu Ft (669 L)	-11.2°F to -1°F (-24°C to -18°C)	2.1A	198.4 lbs (90 kg)	R-290a 4.94 oz (140 g)	2 / 2	115V / 60Hz / 1Ph
MXSH30.0SHC	76 x 35.25 x 35.83 1930 x 895 x 910 mm	30.0 Cu Ft (850 L)	-11.2°F to -1°F (-24°C to -18°C)	2.1A	242.5 lbs (110 kg)	R-290a 5.29 oz (150 g)	2 / 2	115V / 60Hz / 1Ph