MAXX COLD

ICONIC BRANDS, LEADING INNOVATION

Upright Merchandisers
Countertop Merchandisers

010521

www.maxx-cold.com

3355 Enterprise Avenue • Suite 160 | Fort Lauderdale, FL 33331
Tel: 954.202.7419 | Fax: 954.202.7337 | www.maxx-cold.com

A DIVISION OF
THE LEGACY COMPANIES

UPRIGHT MERCHANDISER REFRIGERATORS

MXM1-12RHC
25”W x 26”D x 62”H

MXM1-12RBHC
25”W x 26”D x 62”H

MXM1-16RHC
25”W x 26”D x 74.5”H

MXM1-16RBHC
25”W x 26”D x 74.5”H

MXM1-23RHC
27”W x 32”D x 79.5”H

MXM1-23RBHC
27”W x 32”D x 79.5”H

Models:

MXM1-12RHC - Reach-in refrigerator; white coated steel exterior

MXM1-12RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-16RHC - Reach-in refrigerator; white coated steel exterior

MXM1-16RBHC - Reach-in refrigerator; black coated steel exterior

MXM1-23RHC - Reach-in refrigerator; white coated steel exterior

MXM1-23RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12RHC	25” x 26” x 62” (635 x 660 x 1575 mm)	20.25” x 20.5” x 23.5” (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12RBHC	25” x 26” x 62” (635 x 660 x 1575 mm)	20.25” x 20.5” x 23.5” (514 x 520 x 596 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	3.0A	221 lbs (100 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RHC	25” x 26” x 74.5” (635 x 660 x 1900 mm)	20.25” x 20.5” x 49.125” (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16RBHC	25” x 26” x 74.5” (635 x 660 x 1900 mm)	20.25” x 20.5” x 49.125” (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.0A	243 lbs (110 kg)	R-290A 3.0 oz (85 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23RHC	27” x 32” x 79.5” (686 x 810 x 2019 mm)	26.5” x 22” x 52.25” (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23RBHC	27” x 32” x 79.5” (686 x 810 x 2019 mm)	26.5” x 22” x 52.25” (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	33°F to 41°F (1°C to 5°C)	3.0A	325 lbs (148 kg)	R-290A 3.0 oz (85 g)	1 / 4	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER REFRIGERATORS

MXM2-48RHC
54”W x 32”D x 79.5”H

MXM2-48RBHC
54”W x 32”D x 79.5”H

MXM3-72RHC
81”W x 32”D x 79.5”H

MXM3-72RBHC
81”W x 32”D x 79.5”H

Models:

MXM2-48RHC - Reach-in refrigerator; white coated steel exterior

MXM2-48RBHC - Reach-in refrigerator; black coated steel exterior

MXM3-72RHC - Reach-in refrigerator; white coated steel exterior

MXM3-72RBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48RHC	54” x 32” x 79.5” (1372 x 810 x 2019 mm)	49.25” x 26.5” x 52.25” (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48RHC	54” x 32” x 79.5” (1372 x 810 x 2019 mm)	49.25” x 26.5” x 52.25” (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72RHC	81” x 32” x 79.5” (2057 x 810 x 2019 mm)	72.25” x 26.5” x 52.25” (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72RBHC	81” x 32” x 79.5” (2057 x 810 x 2019 mm)	72.25” x 26.5” x 52.25” (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph

UPRIGHT SLIDING DOOR MERCHANDISER REFRIGERATORS

MXM2-48RSHC
54”W x 32”D x 79.5”H

MXM2-48RSBHC
54”W x 32”D x 79.5”H

MXM3-72RSHC
81”W x 32”D x 79.5”H

MXM3-72RSBHC
81”W x 32”D x 79.5”H

Models:

MXM2-48RSHC - Reach-in sliding door refrigerator; white coated steel exterior

MXM2-48RSBHC - Reach-in sliding door refrigerator; black coated steel exterior

MXM3-72RSHC - Reach-in sliding door refrigerator; white coated steel exterior

MXM3-72RSBHC - Reach-in sliding door refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Double pane insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Supplied with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Equipped with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48RSHC	54” x 32” x 79.5” (1372 x 810 x 2019 mm)	49.25” x 26.5” x 52.25” (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Sliding / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48RSBHC	54” x 32” x 79.5” (1372 x 810 x 2019 mm)	49.25” x 26.5” x 52.25” (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	33°F to 41°F (1°C to 5°C)	4.5A	490 lbs (223 kg)	R-290A 3.7 oz (105 g)	2 Sliding / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72RSHC	81” x 32” x 79.5” (2057 x 810 x 2019 mm)	72.25” x 26.5” x 52.25” (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Sliding / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72RSBHC	81” x 32” x 79.5” (2057 x 810 x 2019 mm)	72.25” x 26.5” x 52.25” (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	33°F to 41°F (1°C to 5°C)	7.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Sliding / 12 Shelves	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER FREEZERS

MXM1-12FHC
25”W x 26”D x 62”H

MXM1-12FBHC
25”W x 26”D x 62”H

MXM1-16FHC
25”W x 26”D x 74.5”H

MXM1-16FBHC
25”W x 26”D x 74.5”H

MXM1-23FBHC
27”W x 32”D x 79.5”H

MXM1-23FBHC
27”W x 32”D x 79.5”H

Models:

MXM1-12FHC - Reach-in refrigerator; white coated steel exterior

MXM1-12FBHC - Reach-in refrigerator; black coated steel exterior

MXM1-16FHC - Reach-in refrigerator; white coated steel exterior

MXM1-16FBHC - Reach-in refrigerator; black coated steel exterior

MXM1-23FHC - Reach-in refrigerator; white coated steel exterior

MXM1-23FBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Triple pane heated & insulated glass door
- Interior LED lighting
- Bottom mounted compressor
- Equipped with three (3) or four (4) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) low profile (1.125" x 1.625") rollers (2 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-12FHC	25” x 26” x 62” (635 x 660 x 1575 mm)	20.25” x 20.5” x 23.5” (514 x 520 x 596 mm)	12 Cu Ft (340 L)	0°F to 10°F (-18°C to -12°C)	5.0A	221 lbs (100 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-12RFBHC	25” x 26” x 62” (635 x 660 x 1575 mm)	20.25” x 20.5” x 23.5” (514 x 520 x 596 mm)	12 Cu Ft (340 L)	0°F to 10°F (-18°C to -12°C)	5.0A	221 lbs (100 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16FHC	25” x 26” x 74.5” (635 x 660 x 1900 mm)	20.25” x 20.5” x 49.125” (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	0°F to 10°F (-18°C to -12°C)	5.0A	243 lbs (110 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-16FBHC	25” x 26” x 74.5” (635 x 660 x 1900 mm)	20.25” x 20.5” x 49.125” (514 x 520 x 1248 mm)	16 Cu Ft (453 L)	0°F to 10°F (-18°C to -12°C)	5.0A	243 lbs (110 kg)	R-290A 3.7 oz (105 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-23FHC	27” x 32” x 79.5” (686 x 810 x 2019 mm)	26.5” x 22” x 52.25” (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	325 lbs (148 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph
MXM1-23FBHC	27” x 32” x 79.5” (686 x 810 x 2019 mm)	26.5” x 22” x 52.25” (673 x 559 x 1327 mm)	23 Cu Ft (651 L)	0°F to 10°F (-18°C to -12°C)	8.0A	325 lbs (148 kg)	R-290A 3.88 oz (110 g)	1 / 4	115V / 60Hz / 1Ph

UPRIGHT MERCHANDISER FREEZERS

MXM2-48FHC
54”W x 32”D x 79.5”H

MXM2-48FBHC
54”W x 32”D x 79.5”H

MXM3-72FHC
81”W x 32”D x 79.5”H

MXM3-72FBHC
81”W x 32”D x 79.5”H

Models:

MXM2-48FHC - Reach-in refrigerator; white coated steel exterior

MXM2-48FBHC - Reach-in refrigerator; black coated steel exterior

MXM3-72FHC - Reach-in refrigerator; white coated steel exterior

MXM3-72FBHC - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Constructed of a powder coated steel exterior and powder coated aluminum interior
- Triple pane, heated, insulated self-closing glass doors
- Interior LED lighting
- Bottom mounted compressor
- Equipped with eight (8) or twelve (12) adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) or six (6) low profile (1.125" x 1.625") rollers (2 or 3 with leveling feet)
- Digital controls with LED temperature display
- Automatic defrost system
- Provided with lock and key set for security
- Illuminated top panel for advertising/promoting products
- Supplied with integrated condensate evaporator therefore no drain line connection is needed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM2-48FHC	54” x 32” x 79.5” (1372 x 810 x 2019 mm)	49.25” x 26.5” x 52.25” (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	6.5A	490 lbs (223 kg)	R-290A 5.29 oz (167 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM2-48FHC	54” x 32” x 79.5” (1372 x 810 x 2019 mm)	49.25” x 26.5” x 52.25” (1251 x 673 x 1327 mm)	48 Cu Ft (1359 L)	0°F to 10°F (-18°C to -12°C)	6.5A	490 lbs (223 kg)	R-290A 5.29 oz (167 g)	2 Swing / 8 Shelves	115V / 60Hz / 1Ph
MXM3-72FHC	81” x 32” x 79.5” (2057 x 810 x 2019 mm)	72.25” x 26.5” x 52.25” (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	0°F to 10°F (-18°C to -12°C)	9.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph
MXM3-72FBHC	81” x 32” x 79.5” (2057 x 810 x 2019 mm)	72.25” x 26.5” x 52.25” (1835 x 673 x 1327 mm)	72 Cu Ft (2039 L)	0°F to 10°F (-18°C to -12°C)	9.0A	670 lbs (305 kg)	R-290A 5.29 oz (150 g)	3 Swing / 12 Shelves	115V / 60Hz / 1Ph

COUNTERTOP MERCHANDISER REFRIGERATORS & FREEZERS

MAXX COLD X-series

MXM1-2RHC
MXM1-2FHC
22.4"W x 22"D x 20.9"H

MXM1-2.5RHC
MXM1-2.5FHC
22.4"W x 22"D x 20.9"H

MXM1-3.5RHC
MXM1-3.5FHC
22.4"W x 22"D x 20.9"H

MXM1-4RHC
MXM1-4FHC
22.4"W x 22"D x 20.9"H

Refrigerators:

MXM1-2RHC - Reach-in refrigerator; coated steel exterior

MXM1-2.5RHC - Reach-in refrigerator; coated steel exterior

MXM1-3.5RHC - Reach-in refrigerator; coated steel exterior

MXM1-4RHC - Reach-in refrigerator; coated steel exterior

Freezers:

MXM1-2FHC - Reach-in freezer; coated steel exterior

MXM1-2.5FHC - Reach-in freezer; coated steel exterior

MXM1-3.5FHC - Reach-in freezer; coated steel exterior

MXM1-4FHC - Reach-in freezer; coated steel exterior

All Models Feature:

- Constructed of white painted steel exterior and ABS interior
- Mutli-pane, self-closing glass door with magnetic compression gaskets
- Interior LED lighting
- Bottom mounted compressor
- Equipped with adjustable heavy-duty PE-coated wire shelves
- Supplied with four (4) adjustable leveling feet
- Digital controls with LED temperature display
- Automatic defrost cycle
- Provided with lock and key set for security
- Foamed urethane insulation to improve temperature regulation
- Supplied with integrated condensate evaporator therefore no drain line connection is needed

MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MXM1-2RHC	22.4" x 22" x 20.9" (569 x 558 x 531 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.1 Cu Ft (59.5 L)	33°F to 41°F (1°C to 5°C)	1.2A	94.8 lbs (43 kg)	R-600A 1.41 oz (40 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-2.5RHC	22.4" x 21.7" x 28.7" (569 x 551 x 729 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.6 Cu Ft (73.5 L)	33°F to 41°F (1°C to 5°C)	1.2A	106.3 lbs (48 kg)	R-600A 1.41 oz (40 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-3.5RHC	24.4" x 22" x 27.2" (620 x 558 x 691 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	3.5 Cu Ft (102 L)	33°F to 41°F (1°C to 5°C)	1.2A	117 lbs (53 kg)	R-600A 1.76 oz (50 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-4RHC	24.4" x 21.7" x 35" (620 x 551 x 889 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	4.2 Cu Ft (119 L)	33°F to 41°F (1°C to 5°C)	1.2A	129 lbs (59 kg)	R-600A 1.7 oz (48 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-2FHC	22.4" x 22" x 20.9" (569 x 558 x 531 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.1 Cu Ft (59.5 L)	0°F to 10°F (-18°C to -12°C)	1.8A	101.4 lbs (46 kg)	R-600A 1.59 oz (45 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-2.5FHC	22.4" x 22" x 28.7" (569 x 558 x 729 mm)	19.3" x 17.3" x 16.5" (490 x 439 x 406 mm)	2.6 Cu Ft (73.5 L)	0°F to 10°F (-18°C to -12°C)	1.8A	115 lbs (52 kg)	R-600A 1.59 oz (45 g)	1 / 2	115V / 60Hz / 1Ph
MXM1-3.5FHC	24.4" x 22" x 27.2" (620 x 558 x 691 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	3.5 Cu Ft (102 L)	0°F to 10°F (-18°C to -12°C)	2.5A	123.5 lbs (56 kg)	R-290A 2.29 oz (65 g)	1 / 3	115V / 60Hz / 1Ph
MXM1-4FHC	22.4" x 22" x 35" (569 x 558 x 889 mm)	21.3" x 17.7" x 22.8" (541 x 450 x 579 mm)	4.2 Cu Ft (119 L)	0°F to 10°F (-18°C to -12°C)	2.5A	143 lbs (65 kg)	R-290A 2.29 oz (65 g)	1 / 3	115V / 60Hz / 1Ph

4-SIDED GLASS COUNTERTOP MERCHANDISER REFRIGERATORS

MECR-31D
16.7"W x 15.9"D x 38.6"H

MECR-32D
16.7"W x 15.9"D x 38.6"H

Models:

MECR-31D - Reach-in refrigerator; white coated steel exterior

MECR-32D - Reach-in refrigerator; black coated steel exterior

All Models Feature:

- Durable, corrosion resistant black painted steel and stainless steel exterior with black plastic trim
- Easy to clean, low maintenance ABS interior
- Dual pane tempered glass doors and sides prevent heat loss and minimize condensation
- Interior LED lighting
- Digital controls deliver precise temperature regulation
- Internal bottom mounted compressor with flow through ventilation to cool the utility compartment
- Manual defrost cycle maintains ideal storage conditions
- Internal condensate evaporator pan included, so no drain connection is needed
- Flat top accommodates POP or other marketing displays
- Three (3) heavy-duty, adjustable chrome-plated wire shelves
- 2" legs (two front adjustable leveling legs)

MODEL	EXTERNAL DIMENSIONS	NOMINAL CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	ELECTRICAL
MECR-31D	16.7" x 15.9" x 38.6" (425 x 404 x 980 mm)	3 Cu Ft (85 L)	33°F to 54°F (1°C to 12°C)	2.0A	84.9 lbs (38.5 kg)	R-290A 1.41 oz (40 g)	1 / 3	115V / 60Hz / 1Ph
MECR-32D	16.7" x 15.9" x 38.6" (425 x 404 x 980 mm)	3 Cu Ft (85 L)	33°F to 54°F (1°C to 12°C)	2.0A	86 lbs (39 kg)	R-290A 1.41 oz (40 g)	2 / 3	115V / 60Hz / 1Ph

Customer Service: : 954.202.7419 | Fax: 954.202.7337
Technical Service: 877-368-2797 | TechnicalServices@TheLegacyCompanies.com