

# MAXX COLD

ICONIC BRANDS, LEADING INNOVATION

**Sandwich / Salad Stations**  
**Megatop Prep Tables**  
**Pizza Prep Tables**



010521



[www.maxx-cold.com](http://www.maxx-cold.com)

3355 Enterprise Avenue • Suite 160 | Fort Lauderdale, FL 33331  
Tel: 954.202.7419 | Fax: 954.202.7337 | [www.maxx-cold.com](http://www.maxx-cold.com)

A DIVISION OF  
THE LEGACY COMPANIES 



**MCR27SHC**

27.5"W x 30"D x 42.54"H

**MCR48SHC**

48.3"W x 30"D x 42.54"H

**MCR60SHC**

60.4"W x 30"D x 42.54"H

**Models:**

**MCR27SHC** - Sandwich station; stainless steel exterior

**MCR48SHC** - Sandwich station; stainless steel exterior

**MCR60SHC** - Sandwich station; stainless steel exterior

**All Models Feature:**

- Durable, easy to clean stainless steel exterior and interior
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 6" swivel casters (2 with brakes)
- Equipped with 4" deep pans (and can accommodate 6" deep pans)
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Equipped with a food grade plastic cutting board and full set of clip-on divider bars and plastic pans
- Self-closing doors
- Polyurethane insulated doors and walls
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	HP	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/6)	ELECTRICAL
MCR27SHC	27.5" x 30" x 42.5" (699 x 762 x 1080 mm)	23.7" x 20.2" x 19.7" (602 x 513 x 500 mm)	7 Cu Ft (198 L)	33°F to 41°F (1°C to 5°C)	3.5A	3/8	198 lbs (90 kg)	R-290a 0.88 oz (25 g)	1 / 1	8	115V / 60Hz / 1Ph
MCR48SHC	48.3" x 30" x 42.5" (1227 x 762 x 1080 mm)	44.7" x 20.2" x 19.7" (1135 x 513 x 500 mm)	13 Cu Ft (386 L)	33°F to 41°F (1°C to 5°C)	3.5A	3/8	284 lbs (129 kg)	R-290a 1.13 oz (32 g)	2 / 2	12	115V / 60Hz / 1Ph
MCR60SHC	60.4" x 30" x 42.5" (1533 x 762 x 1080 mm)	56.7" x 20.2" x 19.7" (1440 x 513 x 500 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.5A	3/8	316 lbs (143 kg)	R-290a 1.13 oz (32 g)	2 / 2	16	115V / 60Hz / 1Ph

# SANDWICH / SALAD STATIONS



### MXCR29SHC

28.9"W x 29.9"D x 43.2"H

### MXCR48SHC

48.2"W x 29.9"D x 43.2"H

### MXCR60SHC

61.2"W x 29.9"D x 43.2"H

### MXCR72SHC

71.7"W x 29.9"D x 43.2"H

#### Models:

**MXCR29SHC** - Sandwich station; stainless steel exterior

**MXCR48SHC** - Sandwich station; stainless steel exterior

**MXCR60SHC** - Sandwich station; stainless steel exterior

**MXCR72SHC** - Sandwich station; stainless steel exterior

#### All Models Feature:

- Stainless steel exterior and powder coated aluminum interior construction
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 3" swivel casters (2 with brakes)
- Equipped with full set of clip-on divider bars and 4" deep plastic pans (not compatible with pans deeper than 4")
- Supplied with 11.42" deep polyethylene cutting board
- Solid state digital control system
- LED temperature display
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/6)	ELECTRICAL
MXCR29SHC	28.9" x 29.9 x 43.2" (699 x 760 x 1098 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	7 Cu Ft (198 L)	33°F to 41°F (1°C to 5°C)	3.0A	218 lbs (99 kg)	R290a 3.0 oz (85 g)	1 / 1	8	115V / 60Hz / 1Ph
MXCR48SHC	48.2" x 29.9 x 43.2" (1225 x 760 x 1098 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	4.3A	304 lbs (140 kg)	R-290a 3.17 oz (90 g)	2 / 2	12	115V / 60Hz / 1Ph
MXCR60SHC	61.2" x 29.9 x 43.2" (1555 x 760 x 1098 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	4.3A	352 lbs (160 kg)	R-290a 3.17 oz (90 g)	2 / 2	16	115V / 60Hz / 1Ph
MXCR72SHC	71.7" x 29.9 x 43.2" (1822 x 760 x 1098 mm)	66.9" x 18.8" x 24.5" (1700 x 478 x 622 mm)	18 Cu Ft (510 L)	33°F to 41°F (1°C to 5°C)	4.3A	430 lbs (195 kg)	R-290a 3.35 oz (95 g)	3 / 3	18	115V / 60Hz / 1Ph



**MXSR29SHC**  
29"W x 30.3"D x 45.4"H



**MXSR48SHC**  
48.4"W x 30.3"D x 45.4"H



**MXSR60SHC**  
61.2"W x 30.3"D x 45.4"H

**Models:**

**MXSR27SHC** - Sandwich station; stainless steel exterior

**MXSR48SHC** - Sandwich station; stainless steel exterior

**MXSR60SHC** - Sandwich station; stainless steel exterior

**All Models Feature:**

- Durable, easy to clean stainless steel exterior and interior
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 6" swivel casters (2 with brakes)
- Equipped with full set of pans
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Equipped with a food grade plastic cutting board and full set of clip-on divider bars and plastic pans
- Self-closing doors
- Polyurethane insulated doors and walls
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT	PAN CAPACITY 1/3 (1/6)	DOORS / SHELVES	ELECTRICAL
MXSR29SHC	29" x 30.3" x 45.4" (735 x 770 x 1152 mm)	24" x 23.4" x 26.6" (610 x 636 x 676 mm)	7.59 Cu Ft (215 L)	33°F to 41°F (1°C to 5°C)	3.6A	150 lbs (68 kg)	R-290a	4 (8)	1 / 1	115V / 60Hz / 1Ph
MXSR48SHC	48" x 30.3" x 45.4" (1230 x 770 x 1152 mm)	43" x 23.4" x 26.6" (1105 x 636 x 676 mm)	13.8 Cu Ft (390 L)	33°F to 41°F (1°C to 5°C)	4.3A	256 lbs (116 kg)	R-290a	6 (12)	2 / 2	115V / 60Hz / 1Ph
MXSR60SHC	61" x 30.3" x 45.4" (1555 x 770 x 1152 mm)	56" x 23.4" x 26.6" (1430 x 636 x 676 mm)	17.8 Cu Ft (505 L)	33°F to 41°F (1°C to 5°C)	5.6A	298 lbs (135 kg)	R-290a	8 (16)	2 / 2	115V / 60Hz / 1Ph



**MCR27MHC**  
27.5"W x 30"D x 44.1"H



**MCR48MHC**  
48.3"W x 30"D x 44.1"H



**MCR60MHC**  
60.4"W x 30"D x 44.1"H

### Models:

**MCR27MHC** - Megatop prep table; stainless steel exterior

**MCR48MHC** - Megatop prep table; stainless steel exterior

**MCR60MHC** - Megatop prep table; stainless steel exterior

### All Models Feature:

- Durable, easy to clean stainless steel exterior and interior
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 6" swivel casters (2 with brakes)
- Equipped with full set of pans
- Automatic defrost system
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Equipped with a food grade plastic cutting board and full set of clip-on divider bars and plastic pans (expanded pan capacity compared to standard sandwich prep tables)
- Self-closing doors
- Polyurethane insulated doors and walls
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	HP	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/6)	ELECTRICAL
MCR27MHC	27.5" x 30" x 44.1" (699 x 762 x 1119 mm)	23.7" x 20.2" x 19.7" (602 x 513 x 500 mm)	7 Cu Ft (198 L)	33°F to 41°F (1°C to 5°C)	3.5A	3/8	223 lbs (101 kg)	R-290a 1.06 oz (30 g)	1 / 1	9	115V / 60Hz / 1Ph
MCR48MHC	48.3" x 30" x 44.1" (1227 x 762 x 1119 mm)	44.7" x 20.2" x 19.7" (1135 x 513 x 500 mm)	13 Cu Ft (386 L)	33°F to 41°F (1°C to 5°C)	3.5A	3/8	318 lbs (144 kg)	R-290a 1.13 oz (32 g)	2 / 2	18	115V / 60Hz / 1Ph
MCR60MHC	60.4" x 30" x 44.1" (1533 x 762 x 1119 mm)	56.7" x 20.2" x 19.7" (1440 x 513 x 500 mm)	16 Cu Ft (453 L)	33°F to 41°F (1°C to 5°C)	3.5A	3/8	362 lbs (164 kg)	R-290a 1.23 oz (35 g)	2 / 2	24	115V / 60Hz / 1Ph



**MXCR29MHC**

28.9"W x 34.5"D x 43.2"H

**MXCR48MHC**

28.9"W x 34.5"D x 43.2"H

**MXCR60MHC**

61.2"W x 34.5"D x 43.2"H

**MXCR72MHC**

71.7"W x 34.5"D x 43.2"H

**Models:**

**MXCR29MHC** - Megatop prep table; stainless steel exterior

**MXCR48MHC** - Megatop prep table; stainless steel exterior

**MXCR60MHC** - Megatop prep table; stainless steel exterior

**MXCR72MHC** - Megatop prep table; stainless steel exterior

**All Models Feature:**

- Stainless steel exterior and powder coated aluminum interior construction
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Equipped with four (4) 3" swivel casters (2 with brakes)
- Supplied with full set of clip-on divider bars and 4" deep plastic pans
- Expanded pan capacity compared to standard sandwich prep tables
- Supplied with 9" deep polyethylene cutting board
- Solid state digital control system
- LED temperature display
- Equipped with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	SHIPPING WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/6)	ELECTRICAL
MXCR29MHC	28.9" x 34.5 x 43.2" (699 x 877 x 1098 mm)	22.9" x 18.8" x 24.5" (602 x 478 x 622 mm)	7 Cu Ft (198 L)	33°F to 41°F (1°C to 5°C)	3.0A	220 lbs (100 kg)	R290a 3.0 oz (85 g)	1 / 1	12	115V / 60Hz / 1Ph
MXCR48MHC	48.2" x 34.5 x 43.2" (1225 x 877 x 1098 mm)	43.5" x 18.8" x 24.5" (1104 x 478 x 622 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	4.3A	304 lbs (140 kg)	R-290a 3.17 oz (90 g)	2 / 2	18	115V / 60Hz / 1Ph
MXCR60MHC	61.2" x 34.5 x 43.2" (1555 x 877 x 1098 mm)	56.2" x 18.8" x 24.5" (1428 x 478 x 622 mm)	15.5 Cu Ft (439 L)	33°F to 41°F (1°C to 5°C)	4.3A	352 lbs (160 kg)	R-290a 3.17 oz (90 g)	2 / 2	24	115V / 60Hz / 1Ph
MXCR72MHC	71.7" x 34.5 x 43.2" (1822 x 877 x 1098 mm)	66.9" x 18.8" x 24.5" (1700 x 478 x 622 mm)	18 Cu Ft (510 L)	33°F to 41°F (1°C to 5°C)	4.3A	430 lbs (195 kg)	R-290a 3.35 oz (95 g)	3 / 3	27	115V / 60Hz / 1Ph

# PIZZA PREP TABLES



**MXCPP50HC**  
47.4"W x 33"D x 41.7"H



**MXCPP70HC**  
70.8"W x 33"D x 41.7"H



**MXCPP92HC**  
94.2"W x 33"D x 41.7"H

### Models:

**MXCPP50HC** - Pizza prep table; stainless steel exterior

**MXCPP70HC** - Pizza prep table; stainless steel exterior

**MXCPP92HC** - Pizza prep table; stainless steel exterior

### All Models Feature:

- Stainless steel exterior and powder coated aluminum interior construction
- Easy to grip recessed door handles
- Adjustable heavy-duty wire shelves (1 per section/door)
- Supplied with four (4) 3" swivel casters (2 with brakes)
- Equipped with full set of clip-on divider bars and 4" deep plastic pans (can accommodate up to 6" deep pans)
- Supplied with 17.75" deep polyethylene cutting board
- Solid state digital control system
- LED temperature display
- Supplied with integrated condensate evaporator therefore no drain line connection is needed
- Urethane foam insulated walls and doors
- Accommodates full-size sheet pans



MODEL	EXTERNAL DIMENSIONS	INTERNAL CABINET DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT AND CHARGE SIZE	DOORS / SHELVES	PANS (1/3)	ELECTRICAL
MXCPP50HC	47.4" x 33 x 41.7" (1212 x 838 x 1059 mm)	26" x 27.75" x 24" (660 x 705 x 610 mm)	12 Cu Ft (340 L)	33°F to 41°F (1°C to 5°C)	5.0A	348 lbs (158 kg)	R-290a 3.7 oz (105 g)	1 / 1	6	115V / 60Hz / 1Ph
MXCPP70HC	70.8" x 33 x 41.7" (1798 x 838 x 1059 mm)	49.5" x 27.75" x 24" (1257 x 705 x 610 mm)	22 Cu Ft (623 L)	33°F to 41°F (1°C to 5°C)	5.0A	432 lbs (196 kg)	R-290a 3.7 oz (105 g)	2 / 2	9	115V / 60Hz / 1Ph
MXCPP92HC	94.2" x 33 x 41.7" (2393 x 838 x 1059 mm)	73" x 27.75" x 24" (1854 x 705 x 610 mm)	32 Cu Ft (906 L)	33°F to 41°F (1°C to 5°C)	5.5A	582 lbs (264 kg)	R-290a 3.7 oz (105 g)	3 / 3	12	115V / 60Hz / 1Ph



**MXSPP50HC**  
47"W x 34.6"D x 42"H



**MXSPP70HC**  
71"W x 34.6"D x 42"H



**MXSPP92HC**  
94"W x 34.6"D x 42"H

**Models:**

**MXSPP50HC** - Pizza prep table; stainless steel exterior

**MXSPP70HC** - Pizza prep table; stainless steel exterior

**MXSPP92HC** - Pizza prep table; stainless steel exterior

**All Models Feature:**

- Exterior Material: Durable, easy to clean stainless steel
- Interior Material: Coated aluminum
- Environmentally friendly, CFC-free urethane foam insulated walls and doors
- Supplied with four (4) 6" swivel casters (2 with brakes)
- Equipped with full set of plastic pans
- Standard recessed door handles
- Heavy duty epoxy coated shelves for easy access and minimal maintenance without disrupting air flow
- Front-accessed utility compartment for easy maintenance & effective air movement to properly cool the condensing unit
- Easily replaceable dart-style magnetic compression gaskets



MODEL	EXTERNAL DIMENSIONS	INTERNAL DIMENSIONS	NET CAPACITY	HOLDING TEMPERATURE RANGE	AMP DRAW	UNIT WEIGHT	REFRIGERANT	PAN CAPACITY 1/3 (1/6)	DOORS / SHELVES	ELECTRICAL
MXSPP50HC	47" x 34.6" x 42" (1200 x 880 x 1068 mm)	25.6" x 27.8" x 26.5" (650 x 707 x 672 mm)	10.9 Cu Ft (310 L)	33°F to 41°F (1°C to 5°C)	4A	201 lbs (91 kg)	R-290a	6 (12)	1 / 1	115V / 60Hz / 1Ph
MXSPP70HC	71" x 34.6" x 42" (1795 x 880 x 1068 mm)	49" x 27.8" x 26.5" (1245 x 707 x 672 mm)	20.9 Cu Ft (592 L)	33°F to 41°F (1°C to 5°C)	5.8A	342 lbs (155 kg)	R-290a	9 (18)	2 / 2	115V / 60Hz / 1Ph
MXSPP92HC	94" x 34.6" x 42" (2390 x 880 x 1068 mm)	72.4" x 27.8" x 26.5" (1840 x 707 x 672 mm)	30.9 Cu Ft (874 L)	33°F to 41°F (1°C to 5°C)	5.8A	485 lbs (220 kg)	R-290a	12 (24)	3 / 3	115V / 60Hz / 1Ph