

# Standard Door Package



### Standard Features

- 100% foamed-in-place polyurethane panels (CFC and HCFC Free)
- UL, NSF, DOE, and EISA compliant
- Flush fit design with gasket for airtight seal
- Adjustable/spring-loaded hinges
- Heated air-vents on freezers, optional on coolers
- Extruded adjustable, flexible sweep gasket to assure seal along the bottom
- Impact resistance FRP door perimeter and jamb
- Steel Reinforced Door Jamb
- LED vapor-proof interior light with constant burn, low wattage nightlight.
   (OSHA approved application – additional switches not required)
- All freezers (5 watts heater) and optional coolers (1 watt heater) heater include an automatic thermostat control (Pepi) for automatic heat adjustment that allows optimal performance

## **Specifications**

#### Standard Door size 34" x 78"

Other widths: 26", 30", 36" <36" see oversized door package Other heights 66", 84", 96" Special sizes may be available upon request

#### **Metal Finishes**

Standard Galvalume Interior and/or exterior See Metal Sample Flyers for full listing

#### **Hardware**

Kason 28 Deadbolt Locking Handle
Antimicrobial, pad lockable
Kason 1346 Radius Hinges
Auto close, spring-loaded, adjustable
Kason 1094 Hydraulic Actuated Closer
Individual item specs available upon request

#### Accessories

2" dial thermometer Switch with pilot light Kason 1803 LED Door Section Light with 1802NL

*Individual item specs available upon request* 

