

ITEM NO:	
PROJECT:	
DATE:	

## **Non-Refrigerated Service Case**



□ NR3647DSV□ NR4847DSV

Lengths include end panels 35-3/4"L x 33"D x 47-1/8"H 47-3/4"L x 33"D x 47-1/8"H

## STANDARD FEATURES

- NOTE: Glass warranty only applicable to first point of delivery
- (2) Levels of clear glass shelving removable and adjustable on 1" centers
- LED top & shelf lights
- One piece formed ABS plastic tub
- One year parts & labor warranty
- Vertical, fixed front & side UV bonded frameless glass

Features	Standard	Options
EXTERIOR COLOR	□ Black	<ul> <li>□ Painted (non-stock colors, specify RAL#)</li> <li>□ Painted (stock colors, specify RAL#)</li> <li>□ Stainless steel</li> </ul>
INTERIOR COLOR	□ Black	<ul> <li>□ NOTE: Interior color must be FDA &amp; NSF approved</li> <li>□ Painted (stock colors, specify RAL#)</li> <li>□ Stainless steel</li> </ul>
PANEL EXTERIOR	□ Laminated (non-premium) Confirm pattern/grain direction	<ul> <li>□ Laminated (premium) Confirm pattern/grain direction</li> <li>□ Stainless steel</li> </ul>
BASE SUPPORT	□ Adjustable, locking casters	□ 6"H stainless steel legs
END PANEL LEFT	□ Full end panel	□ No end panel
END PANEL RIGHT	□ Full end panel	□ No end panel
LOWER FRONT PANEL	□ Black	□ Painted (stock colors, specify RAL#) □ Stainless steel
LOWER REAR PANEL	□ Black	<ul><li>□ Painted (stock colors, specify RAL#)</li><li>□ Stainless steel</li></ul>
UPPER REAR	□ Clear glass rear sliding doors	□ Reflective glass rear sliding doors
LIGHTS	□ LED 3500K w/ frosted lens	□ LED 3000K w/ frosted lens □ LED 4000K w/ frosted lens
ELECTRICAL CONNECT	□ 12" Straight blade power cord	<ul><li>12" Locking power cord</li><li>Electrical leads (non-refrigerated)</li></ul>
MISCELLANEOUS		□ 14.5" Base height extension □ Rear door lock □ Second year parts & labor warranty

Option Notes: 1 - Cannot be combined w/ 6"H legs

888 E. Porter Rd.





Intended Environment: Type I - Designed to operate in ambient conditions of 75°F with 55% relative humidity unless noted otherwise in system information below.


Intended Product To Be Displayed Warmest Avg Prod Temp ° F Zone Unpackaged non-refrigerated products

**PLAN VIEW** 

Ambient SIDE VIEW







## NOTE: ALL DIMENSIONS APPROXIMATE

ELECTRICAL JUNCTION BOX (SUPPLIED WITH 6" LEADS OR POWER CORD).

LOCATION OF DRAIN TUBE FOR REMOTE REF. ONLY (SUPPLIED WITH 3," OR 11;" PVC TUBE).

REFRIGERATION LINE CONNECTION.

SELF-CONTAINED CASE SERVICE ACCESS AREA.

REMOTE FLOOR SINK & UTILITIES ACCESS AREA. DRY CASE SERVICE ACCESS AREA.

	Model Technical Specifications															
Model	L"	L1"	L2"	System	Circuit Volts		Phs	Freq	Amps	Watts	Wires	NEMA Plug	SST	Conv. Rack BTUH	Para. Rack BTUH	Est Wt
NR3647DSV	N/A	35.75	.00	Ambient/Lights	Circuit #1	110-120	1	60	0.70	11	2+G	5-15P or L5-15P	N/A	N/A	N/A	650
NR4847DSV	N/A	47.75	.00	Ambient/Lights	Circuit #1	110-120	1	60	0.70	17	2+G	5-15P or L5-15P	N/A	N/A	N/A	750

<sup>\*\*\*</sup> Does not include electric defrost on freezer models.

Regulatory Approvals:					
All Models	ETL Listed to UL 65				
	FTL Sanitation to NSF 2				



**Important Notes:** 

- 1) ELECTRICAL NOTE: If GFCI is required, a GFCI breaker MUST be used in lieu of a GFCI receptacle
- 2) Glass warranty only applicable to first point of delivery.

MARNING: This product can expose you to chemicals, including Urethane (Ethyl Carbamate), which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.