

Medical+Pro



Medical Grade Refrigerators

Self-Closing Swing Glass Door with Double Pane Low-E Glass and Lock
 Digital Temperature Read-Out and Controller
 Adjustable Operating Temperature Range from 1°C to 10°C
 2 Temperature Probes
 Audible Hi/Low Alarm
 Interior LED Lights
 Interior Plenum for Uniform Air Distribution on MP-22RM-HC and MP-44RM-HC
 90° Hold Open Door Feature
 All Natural R290 Hydrocarbon Refrigerant
 Recessed Door Handles
 Forced-Air Refrigeration System
 Bottom Mount Compressor
 White Powder-Coated Interior & Exterior
 Pre-installed Adjustable Shelving
 7/8" Access Port
 Glycol Product Simulator Bottle & Bracket
 All Units 115/60/1 Volt, NEMA 5-15P Plug
 Warranty - 5 yrs Compressor, 1 yr Parts & Labor
 4 Casters

MODEL	DOORS	CAPACITY CU/FT	SHELVES	H/P	AMPS	VOLTAGE	ENERGY CONSUMPTION KWH/24HR	TEMP RANGE (°C)	EXTERIOR DIMENSIONS W X D X H" <small>*Casters included in height</small>	INTERIOR DIMENSIONS W X D X H"	WEIGHT
MP-10RM-HC	1	10	3	1/7+	4	115/60/1	1.7	1°C to 10°C	24.25" x 24" x 60.25"	19.75" x 20.25" x 37"	225 lbs
MP-12RM-HC	1	12	4	1/7+	4	115/60/1	2.79	1°C to 10°C	24.25" x 24" x 76.25"	19.75" x 20.25" x 48"	235 lbs
MP-22RM-HC	1	22	4	1/7+	6.1	115/60/1	1.7	1°C to 10°C	27" x 31.5" x 82.92"	22.2" x 25.1" x 60"	265 lbs
MP-44RM-HC	2	44	8	1/5	7	115/60/1	3.4	1°C to 10°C	54.4" x 31.5" x 82.87"	49.7" x 25.1" x 60"	445 lbs

Medical+Pro reserves the right to change specifications without notice.



1.856.477.3991

MedProScientific.com



*Ships standard LTL free freight. Accessories such as lift gate or limited access deliveries will be charged an extra fee.