



The Signature of Quality

FEDERAL INDUSTRIES

A Standex Company
215 Federal Avenue
Belleville, WI 53508-9201

Phone: 800-356-4206
Fax: 608-424-3234
Email: geninfo@federalind.com
Website: www.federalind.com

Project Name: _____

Item #: _____

Model #: _____ Qty: _____

Approval: _____

AIA#

SIS#

HYBRID MERCHANDISER

SERVICE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

MODEL	DIMENSIONS (Includes End Panels)
<input type="checkbox"/> CD3628/RSS3SC	36.25x 39 x 69.75 (in) 921 x 991 x 1772 (mm)
<input type="checkbox"/> CD4828/RSS4SC	48 x 39 x 69.75 (in) 1219 x 991 x 1772 (mm)
<input type="checkbox"/> (2)CD3628/RSS6SC	72 x 39 x 69.75 (in) 1829 x 991 x 1772 (mm)

Display more product and serve more customers with presentation and value in mind.



SELF-SERVE NON-REFRIGERATED OVER SELF-SERVE REFRIGERATED

MODEL	DIMENSIONS (Includes End Panels)
<input type="checkbox"/> CD3628SS/RSS3SC	36.25 x 39 x 69.75 (in) 921 x 991 x 1772 (mm)
<input type="checkbox"/> CD4828SS/RSS4SC	48 x 39 x 69.75 (in) 1219 x 991 x 1772 (mm)
<input type="checkbox"/> (2)CD3628SS/RSS6SC	72 x 39 x 69.75 (in) 1829 x 991 x 1772 (mm)

STANDARD FEATURES

Refrigerated Self-Serve Bottom Display

- Black laminated exterior. Other finishes available.
- Black trim. Silver optional.
- Black interior, glass ends.
- Horizontal LED top and front light.
- Two tiers black metal shelves.
- Electronic temperature control maintains 38° to 40° case temperature. Note: Case temperature will vary if the air curtain is disrupted.
- Cord and plug. (Not available on RSS6SC.)
- Condensate evaporator (separate circuit required on model RSS6SC)
- R513a Refrigerant

Service or Self-Serve Non-Refrigerated Top Display

- Two tiers black wire shelves.
- Sliding rear doors.
- Black trim.
- Self-Serve has three hinged lift-up front doors.

Lighting

- LED top light and shelf lights.

Agency Approvals

- UL Safety and UL Sanitation Listed to NSF Type II conditions.
- DOE 2017 Compliant

OPTIONAL ACCESSORIES

For Top Display

- Glass Shelves
- Reflective Ends
- Reflective Rear Doors

For Self-Serve Refrigerated Base

- Energy Saving Night Curtain
- Silver Trim
- Special Base Finish
- Mirrored Interior Ends
- Security Night Cover
- Stainless Steel Steps in Lieu of Metal Shelves
- Reflective End Glass



WARRANTY*
One year Parts and Labor
2nd thru 5th year part
only service compressor
(U.S.A and Canada)

Note: Information is subject to change at any time.
Visit www.federalind.com for the most current specs.

AIA#	HYBRID MERCHANDISER
SIS#	Product Specifications



Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.

Zone	Intended Product To Be Displayed	Avg Prod Temp °F/°C
All	Packaged Refrigerated Products	38°F / (3.3°C)

DIMENSION: xx"/(mm)
 DIMENSION TOLERANCE +/- 0.19 (4.8)

**SERVICE NON-REFRIGERATED
 OVER SELF-SERVE REFRIGERATED**

**SELF-SERVE NON-REFRIGERATED
 OVER SELF-SERVE REFRIGERATED**



MODEL	DIMENSIONS				SHIPPING WHT		BOTTOM DISPLAY	TOP DISPLAY
	L	D	H	UNITS	LBS	KILO	120/60/1 (NEMA 5-20P)	120/60/1 (NEMA 5-15P)
CD3628/RSS3SC	36.25	39	69.75	in.	847	384	1/3 HP - 14.8 AMPS	1.5 AMPS
	921	991	1772	mm.				
CD4828/RSS4SC	48	39	69.75	in.	1,010	458	1/2 HP - 16.0 AMPS	1.5 AMPS
	1219	991	1772	mm.				
(2)CD3628/RSS6SC*	72	39	69.75	in.	1,500	680	3/4 HP - 16.0 AMPS	(2) 1.5 AMPS
	1829	991	1772	mm.				
CD3628SS/RSS3SC	36.25	39	69.75	in.	790	358	1/3 HP - 14.8 AMPS	1.5 AMPS
	921	991	1772	mm.				
CD4828SS/RSS4SC	48	39	69.75	in.	900	408	1/2 HP - 16.0 AMPS	1.5 AMPS
	1219	991	1772	mm.				
(2)CD3628SS/RSS6SC*	72	39	69.75	in.	1,300	590	3/4 HP - 16.0 AMPS	(2) 1.5 AMPS
	1829	991	1772	mm.				

- * On the RSS6SC a separate 120/60/1 15 AMP circuit is required for the condensate evaporator.
- If a GFCI circuit is required, a GFCI Breaker Must be used instead of GFCI recepticle.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.a



FEDERAL INDUSTRIES
 A Standex Company
 215 Federal Avenue Belleville, Wisconsin 53508-9201

Phone: 800-356-4206
Fax: 608-424-3234
Email: Geninfo@Federalind.com
Website: Federalind.com