

FEDERAL INDUSTRIES

A Standex Company 215 Federal Avenue Belleville, WI 53508-9201

Phone: 800-356-4206 Fax: 608-424-3234 Email: geninfo@federalind.com

Project Name: _		
Item #:		
Model #:	Qty:	SIS#
Approval:		

SELF-SERVE REFRIGERATED PREPARED FOODS MERCHANDISER

Website: www.federalind.com

Designed for those customers looking for up-market styling for maximum visual appeal that will drive product sales.



Model SSRPF5952 Shown

OPTIONAL ACCESSORIES

- □ Reflective End Glass
- ☐ Special Exterior Finish
- ☐ Glass Shelves
- □ Energy Saving Night Curtain
- ☐ Security Night Cover
- ☐ Solid Rear Sliding Access Doors
- □ Cord & Plug

- □ Remote Refrigeration (EEV Included)
- □ Recessed Casters
- □ Condensate Pump
- ☐ Joining Kit for Continuous Line-ups
- ☐ Front Non-Refrigerated Display Merchandiser

WARRANTY*

□ Legs

MODEL	DIMENSIONS (Includes End Panels)
□ SSRPF3652	36 x 34 x 52 (in)
	914 x 864 x 1321 (mm)
□ SSRPF5052	50 x 34 x 52 (in)
	1270 x 864 x 1321 (mm)
□ SSRPF5952	59 x 34 x 52 (in)
	1499 x 864 x 1321 (mm)
□ SSRPF7752	77 x 34 x 52 (in)
	1956 x 864 x 1321 (mm)

AIA#

STANDARD FEATURES

Model Features

- Steel base construction with black laminated exterior. Other finishes optional.
- Black interior, glass end panels
- Easily accessible light and power switch.
- Rear access to refrigeration system for quick and easy service
- The rear of the display needs to be 6" from wall.
- Adjustable leg levelers

Refrigeration

- On-demand PTC condensate evaporator provided for a totally self-contained system
- Electronic temperature controls maintain 38°-40° F with on-demand defrost. Note: Case temperature will vary if the air curtain is disrupted.
- Easy clean, rustproof insulated evaporator coil compartment
- R449a refrigerant
- Thermometer

Shelving

• Three tiers adjustable metal shelves

LED top light and shelf lights

Agency Approvals

- UL and UL Sanitation listed
- DOE 2017 Compliant











AIA#

SELF-SERVE REFRIGERATED PREPARED FOODS MERCHANDISER

SIS#


Specifications


Intended Environment: Type I - Designed to operate in maximum ambient conditions of 75°F (24°C) and 55% relative humidity unless noted otherwise in system information below.


Zone	Intended Product To Be Displayed	Avg Prod Temp °F/°C
All	Packaged Refrigerated Products	38°F / (3.3°C)


DIMENSION: xx"/(mm)

DIMENSION TOLERANCE +/- 0.25 (6.4)









MODEL	DIMENSIONS			SHELVES	SHIPPING WHT		SELF CONTAINED Permanently Connected			OPTIONAL NEMA PLUG	REMOTE WITH CONDENSATE PAN		
	L	D	H1	UNITS		LBS	KILO	VOLTAGE	AMPS	H.P.	CONFIG (SC)	VOLTAGE	AMPS
SSRPF3652	36	34	52	in.	4	590 268	200	268 120/60/1	15 AMPS	1/3 HP	NEMA 5-20P	120/60/1	9 AMPS
	914	864	1321	mm.			208						
SSRPF5052	50	34	52	in.	4	720	327	208-240/60/1	10 AMPS	1/2 HP	NEMA 6-15P	120/60/1	10 AMPS
	1270	864	1321	mm.									
SSRPF5952	59	34	52	in.	4	845 3	202	383 208-240/60/1	15 AMPS	1/2 HP	NEMA 6-20P	120/60/1	13 AMPS
	1499	864	1321	mm.			363						
SSRPF7752	77	34	52	in.	4	1010 45	450	208-240/60/1	15 AMPS	3/4 HP	NEMA 6-20P	120/60/1	14 AMPS
	1956	864	1321	mm.			458	208-240/60/1					

- Case temperature will vary if the air curtain is disrupted.
- The rear of the unit needs to be 6" from a wall.
- Electrical Requirement The minimum circuit ampacity and maximum fuse size is 20 amps.
- Refrigerated cases are designed to operate in a maximum of 75°F (24°C) ambient and 55% relative humidity.
- Due to continuing engineering improvements, specifications are subject to change without notice.









Phone: 800-356-4206 **Fax:** 608-424-3234

Email: Geninfo@Federalind.com **Website:** Federalind.com