		Project Name:	AIA#:
	Model #: _	Location:	
SIS#:		Item #: Quantity:	

Vacuum Packaging **Machines**

Food storage & food prep made easier!

Vacuum seal perfect portion sizes for long-lasting freshness, or prep for sous vide cooking!

1100e



GVP6 - Standard 6 m3/h pump capacity GVP20 - Standard 20 m³/h pump capacity GVP20A - Advanced 20 m³/h pump capacity

Standard Features

- Digital display clearly shows vacuum & sealing times
- Timed vacuum cycle up to 50 seconds and timed sealing up to 4.5 seconds
- Domed lid for durability and larger product capacity
- Two elevation platforms included to align product with sealing bar
- Seal bar easily removed for cleaning in all locations
- Rounded steel tank with no seals or edges for easy
- Stop & Seal button allows operator to complete and seal product before end of cycle
- Stop button allows operator to cancel cycle
- Non-slip, non-scratch rubber feet

Advanced Features

- LED display screen with 5 language options
- Marination preset for intermittent vacuum with marinade which introduces more flavor into meats in a fraction of the time
- Cycle can be set for vacuum time or vacuum percentage
- Gas Flush increases shelf life preventing discoloration of certain products, protects fragile products and limits microorganism growth
- Gastronorm function for sealing external pans

Warranty

1-year parts and labor warranty

Optional Accessories

- VPBS610 3.5 mil 6"x10" storage bags, 1000/box
- VPBS812 3.5 mil 8"x12" storage bags, 1000/box
- VPBC612 3.5 mil 6"x12" cooking bags, 1000/box
- VPBC812 3.5 mil 8"x12" cooking bags, 1000/box

Storage Bags suitable for packing solids, liquids, and delicate products. Should not be used over 100°F; not appropriate for cooking.

Cooking Bags specifically designed for temps between -40°F & 250°F. Excellent for Sous-Vide cooking and a cook/chill process.

To select options see back














Approved by:	Date:
, –	














SPECIFICATIONS						
Model	Pump Capacity	Motor	Amps	Volts	Capacity	
wodei					Chamber Size	Sealing Bar Length
GVP6	6 m³/h	1 HP	4.7	120/60/1	10.6" x 13.7" x 7.5" (27 cm x 35 cm x 19 cm)	10.2 " (26 cm)
GVP20	20 m³/h	1.6 HP	9.5	120/60/1	16.75" x 17" x 8.6" (42.6 cm x 43.2 cm x 21.8 cm)	16.5" (42 cm)
GVP20A	20 m³/h	1.6 HP	9.5	120/60/1	16.75" x 17" x 8.6" (42.6 cm x 43.2 cm x 21.8 cm)	16.5" (42 cm)

Cord & Plug: Attached 6 foot flexible 3-wire cord with molded plug fits a grounded receptacle. NEMA 5-15 ()

DIMENSIONS SHIPPING INFORMATION					
Item ships in	reinforced box. Freight Class 100				
Model	Overall Dimensions	Net Weight	Shipping Dimensions	Shipping Weight	
GVP6	13.625" W x 18.375" D x 28.25" H (34.6 cm x 46.7 cm x 71.75 cm)	60 lbs. (27.2 kg)	19.7" W x 22" D x 56" H (50 cm x 56 cm x 50 cm)	70.5 lbs. (32 kg)	
GVP20	20.25" W x 22" D x 35" H (51.4 cm x 56 cm x 88.9 cm)	133 lbs. 60.3 kg)	24" W x 26.4" D x 25.2" H (61 cm x 67 cm x 64 cm)	145.5 lbs. (66 kg)	
GVP20A	20.25" W x 22" D x 35" H (51.4 cm x 56 cm x 88.9 cm)	133 lbs. (60.3 kg)	24" W x 26.4" D x 25.2" H (61 cm x 67 cm x 64 cm)	145.5 lbs. (66 kg)	

OPTIONAL ACCESSORIES

- **VPBS610** 3.5 mil 6"x10" storage bags, 1000/box
- ☐ VPBC612 3.5 mil 6"x12" cooking bags, 1000/box
- ☐ VPBS812 3.5 mil 8"x12" storage bags, 1000/box

☐ VPBC812 3.5 mil 8"x12" cooking bags, 1000/box

Globe Vacuum Packing Machines feature digital displays showing vacuum and sealing times. Vacuum time up to 50 seconds, sealing time up to 4.5 seconds. Pistons built into lid automatically open when sealing is complete. Stop and Stop & Seal buttons to cancel cycle mid-vacuum. Rounded steel tank for easy cleaning. Heating element removes for easy cleaning. Non-slip, non-scratch feet. Units are CSA design certified, NSF and ETL listed. Oneyear parts and labor warranty.

2153 Dryden Rd., Dayton, OH 45439

937-299-5493 | 800-347-5423 | Fax: 937-299-4147 | www.globefoodeguip.com