

LX-74RS TRIPLE GLASS DOOR MERCHANDISER REFRIGERATOR

Energy efficient, eco-friendly HC refrigerant with low charge, spark-free components, and the lowest utility costs in its category.



KEY FEATURES



Eco-Friendly Refrigerant

Environmentally friendly R290 hydrocarbon refrigerant has low Global Warming Potential (GDP). Meets all USA, California & Canada refrigerant & energy standards.



Intelligent Electronic Control

Patented ETC1H electronic controller assures optimal refrigeration performance through precision temperature control, and intelligent control for defrost cycle, compressor & other component functions.



• High Power Reliable Refrigeration System

Fast pull down, optimal internal air circulation and reliable refrigeration, maintaining cooler temperatures for food preservation.



Standard LED Lighting System

Ultra bright low energy interior LED illumination system provides optimal merchandise display visibility. Low profile, door mounted, clip-in LED design.



• Newly Designed Condenser

New condenser featuring a joints reduction down to zero increasing long term refrigeration reliability and safeguarding against any system leaks.



Spark-Free Refrigeration Components

All Reach-In models have spark free refrigeration components for optimal safety, per UL requirements.

















3560 NW 56th Street Fort Lauderdale, FL, United States 33309 Telephone: 786.600.4687 / Toll Free: 844.218.8477 Fax: 786.661.4100 5659 Royalmount Ave. Montreal, QC, Canada H4P 2P9 Telephone: 514.737.9701 / Toll Free: 888.275.4538 Fax: 514.342.3854 / Toll Free: 877.453.8832 sales@mvpgroupcorp.com / mvpgroupcorp.com



LX-74RS TRIPLE GLASS DOOR MERCHANDISER REFRIGERATOR

PRODUCT VIEWS





Top

FIOR

ADDITIONAL FEATURES



Manual Lock - External lock available



Gravity kit - Visi-Slide product display technology



Price Kit - Available for shelf display



Casters or legs are available options

TECHNICAL SPECIFICATIONS

Exterio	r Dimensio	ons	Interio	Interior Dimensions		
W:	78 3	3/4" (200 cm)	W:	W: 74 5/8" (190 cm)		
D:	33	5/8" (86 cm)	D:	27	1/4" (69	cm)
H:	79 3	3/8" (202 cm)	H:	H: 60 1/8" (152 cm)		
Usable	Interior Ca	pacity	Usable	Usable Volume		
W:	72 1	1/8" (183 cm)			c F.	
D:	21	5/8" (55 cm)		66.3 Cu Ft 1878.4 L		
H:	52 5	5/8" (134 cm)		10/0.41		
Doors		Material	Shelve	25	Shelf	Size
						244/4//

3	Plastic Frame	15	W:	24 1/4" (62 cm)
ý			D:	22 1/8" (56 cm)
Exterior Material		430 Stainless Steel		

Interior Material 201 Stainless Steel

REFRIGERATION PERFORMANCE

Refrigerant	Energy Consumption	
R290 / 5.6 oz (0.160 kg)	5.004 kWh/24h	
Compressor Power	Condenser	
1/2 HP x2	Finless (low maintenance)	
Thermostat default setting	32°F (0°C) to 44.6°F (7°C)	

ELECTRICAL

Power Supply	Amps	Lighting	
115V/60Hz	8.7A	242 Lux Output 27 modules, 8 LED per	
Plug Type	Controller	Cord Length	
NEMA 5-15P	ETC1H	128" (327 cm)	

LOGISTICS

Trailer Loads Unit Weight		Shipping Dimensions		
	815.7 lb (370 kg)	W:	81 1/4" (206 cm)	
53′: 18	Shipping Weight	D:	33 3/4" (86 cm)	
	828.9 lb (376 kg)	H:	82 3/4" (210 cm)	