

















FRG2VE

FRG4VE

FRG6VE

- All Stainless-Steel construction
- Sliding tempered glass doors
- Stainless-Steel V skewers, no hook required
- 2 Stainless-Steel grease drawer collectors
- FRG4VE and FRG6VE 3" caster included
- FRG2VE and FRG8VE legs included
- Independent motor per spit
- Motor rotation 2 rpm
- Capacity 5 chickens or 40 lbs. per spit
- Cooking time 50 to 60 min (calculated with 4 lbs. birds)

## Ovens equipped only with V spit skewers

Easy, clean, no tools required, secure, quick load and unload chickens

## Installation Notes:



- At least a 5" clearance is needed on oven's rear, left and right side for proper performance.
- Ovens are top-vented, operated under a hood or direct exhaust (where permitted)

	FRG2VE	SPECIFICATIONS FRG4VE	FRG6VE	FRG8VE
Chickens capacity	10	20	30	40
Voltage	110V/50-60hz/1ph	110V/50-60hz/1ph	110V/50-60hz/1ph	110V/50-60hz/1ph
Plug	Nema 15 <b>-</b> 5	Nema 15 <b>-</b> 5	Nema 15-5	Nema 15-5
Amps	1.2	1.8	3.6	4.8
Power (Btu)	30,000	60,000	90,000	120,000
External Dim WxDxH (inch)	46x24x31	46x24x58	46x24x65	46x24x70
Weight (lbs)	137	227	271	302
Shipping Dim WxDxH	47x25x32	47x25x59	47x25x66	47x25x75
Shipping Weight (lbs)	167	267	271	302