



Sleek Shields™

MULTI-USE FOOD SHIELDS WITH GLASS TOP

Quickly Converts From Cafeteria Style To Self Serve Style

ltem #:	Qty #:
Model #:	
Project #:	



FEATURES:

- Bottom front glass locks in place at 3 fixed positions
- Entire glass front rotates for easy cleaning
- Stainless steel 1" diameter Posts
- Includes Two 18" Wide Glass Side Panels
- 1/4" Thick Heat-Tempered Glass Side Panels
- 3/8" Thick Heat-Tempered Glass Fronts
- 3/8" Thick Heat-Tempered Glass Top

CONSTRUCTION:

All TIG welded

Exposed stainless steel surfaces polished to a satin finish

MATERIAL:

1/4" Thick Heat-Tempered Side Glass

3/8" Thick Heat-Tempered Glass Fronts and Top

1" Posts - Stainless Steel

Chamber Lock™ Sleek Shield Assemblies - Anodized Aluminum. Finish - Aluminum components are anodized to a satin finish. Stainless components polished.



Bottom Glass Flips All The Way Up To Become A Self-Serve Unit



Bottom Glass Can be Used As a Shelf



Easy To Use Mechanism For Changing Front Glass Positions



Entire Glass Shield Rotates For Easy Cleaning

		Approx.		Approx.		Approx.	Approx.	
L	12" WIDE	Wt.	15" WIDE	Wt.	18" WIDE	Wt.	Cubes	
36"	DSG-12G-36	139 lbs.	DSG-15G-36	143 lbs.	DSG-18G-36	147 lbs.	18	
48"	DSG-12G-48	179 lbs.	DSG-15G-48	182 lbs.	DSG-18G-48	187 lbs.	23	
60"	DSG-12G-60	228 lbs.	DSG-15G-60	235 lbs.	DSG-18G-60	242 lbs.	29	
72"	DSG-12G-72	279 lbs.	DSG-15G-72	266 lbs.	DSG-18G-72	275 lbs.	34	
84"	DSG-12G-84	298 lbs.	DSG-15G-84 [†]	305 lbs.	DSG-18G-84 [†]	316 lbs.	39	
96"	DSG-12G-96 [†]	330 lbs.	DSG-15G-96 [†]	346 lbs.	DSG-18G-96 [†]	357 lbs.	44	
108"	DSG-12G-108 [†]	373 lbs.	DSG-15G-108 [†]	383 lbs.	DSG-18G-108 [†]	397 lbs.	49	
120"	DSG-12G-120 [†]	412 lbs.	DSG-15G-120 [†]	424 lbs.	DSG-18G-120 [†]	439 lbs.	55	
132"	DSG-12G-132 [†]	453 lbs.	DSG-15G-132 [†]	467 lbs.	DSG-18G-132 [†]	483 lbs.	60	
144"	DSG-12G-144 ^{††}	495 lbs.	DSG-15G-144 ^{††}	511 lbs.	DSG-18G-144 ^{††}	528 lbs.	65	

† Requires a single pair of center legs † Requires two pair of center legs



Customer Service Available To Assist You 1-800-645-3166 8:30 am - 7:00 pm E.S.T.

For Orders & Customer Service:

Email: customer@advancetabco.com or Fax: 631-242-6900

For Smart Fabrication™ Ouotes:

Email: smartfab@advancetabco.com or Fax: 631-586-2933

DETAILS and SPECIFICATIONS

TOL ± .500" ALL DIMENSIONS ARE TYPICAL



