

GLASS DOOR MERCHANDISER REFRIGERATOR SINGLE SWING DOOR

Project Location:

Project Name:

Model #:_ ___ Quantity: ____

Available Warehouse:_

EM Series Model: EMGR8





Refrigeration System

Bottom mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.

- Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.
- Full-length air duct ensures optimal cold air distribution.
- Air circulation guard keeps floor vents from obstruction.
- Time-initiated and temperature-terminated auto defrost cycle for seamless operation.
- Large capacity, corrosion-resistant condenser and evaporator coils. Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.

High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning.

· Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

Cabinet Construction

- Heavy duty white coated steel interior / exterior.
 Open spaced interior with no walls between compartments.
- · Stainless steel floor interior has rounded corners and detachable drain plug for ease of cleaning.
- 2.5" thick high density polyurethane insulation.
- · Four height adjustable screw legs.

Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

Doors

- · Low emissivity double glass panes reflect UV rays for efficient cooling.
- · Black PVC door frames.
- · Self-closing with adjustable torsion system for a positive seal.
- Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, die-cast door handles.

Shelving

- · Epoxy coated, steel wire shelves with airflow guard (see table for quantity).
- · Height adjustable stainless steel clips.

Temperature Control

- · Multi-function digital controller with easy to read LED display.
- · Factory preset temperature, 35°F. Temperature setting range from 33°F to 54°F.
- Audible overheat protection alarm for compressor and condenser coil.

Options

- · Additional shelving.
- · Wine rack (applies to model EMGR24 and EMGR24B).
- 5" or 3" swivel casters with locks on front set.
- · 3.5" 6" height-adjustable and interchangeable legs.



Please visit our website for updated Energy Efficiency information

	Ref/	Doors	Capacity		Shelves Refrigerant	HP	Power	Amps	Crated	Exterior Dimensions			
Frz/Dual	20013	Cu. Ft.	20 oz. Bottles	nonigorant			V-Hz-Ph	Allipo	Weight	L	D	H*	
Γ	REF	1	8	90	2	R-290	1/4+	115-60-1	2.5	205 lbs (93kg)	24" (610mm)	24.375" (619mm)	61.375" (1559mm)

(†) Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (★) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.



GLASS DOOR MERCHANDISER REFRIGERATOR

SINGLE SWING DOOR

EM Series

Model: EMGR8

DIMENSIONAL DATA

	L	24" (610mm)			
External Dimensions	D	24.375" (619mm)			
	H*	61.375" (1559mm)			
Crated Weight		205 lbs. (93kg)			
Doors/Drawers/Lids		1			
Max Weight Support (LBS)	-			
STORAGE DATA					
Net Capacity Cu. Ft. 🏲		8			
Shelves		2			
Barrels		-			
20 oz. Bottles		90			
12 oz. Bottles		-			
12 oz. Cans		-			
8" Mugs		-			
# of Pans (Top)		-			
# of Pans (Drawer)		-			
Dividers Trays		-			
		-			

ELECTRICAL DATA

Voltage	115-60-1
Full Load Amperage	2.5A
Feed Wires with Ground	3
Cord Length	9ft
NEMA Plug Type	•• NEMA 5-15P


REFRIGERATION DATA

Compressor Mounting	Bottom
Refrigerant	R-290
Compressor HP	1/4+
BTU/HR [†]	N/A


KEY

D Door L Lid H Half D FD Full Dd SD Solid I GD Glass	oor FRZ Door DUAL	Refrigerator Refrigerator Freezer Freezer REF/FRZ Combo Drawer
---	----------------------	---


	Elevation	Right	Plan	3D	Back
KCL					



PLAN VIEW







ACCESSORIES & OPTIONS

Part Number	Description		
Additional Shelving	Contact Everest Refrigeration for more information.		
AJL03-00	Interchangeable Leg for Caster (Optional)		
CASA3-01	3" Overall Height Caster Assembly - (2) Front (2) Rear		
CASA5-01	5" Overall Height Caster Assembly - (2) Front (2) Rear		
Left Hinged Door	Contact Everest Refrigeration for more information.		

F. (310) 323-7524

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (►) Product capacity is calculated based on standard industry figures. (★) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.

VER. 1/6/2023