

Project:	Quantity:
Model #:	Approval:

# CR36-6 36" 6 Burner Gas Range with Oven



## **FEATURES**

- Stainless steel front, sides, back riser and shelf
- Cast iron open lift off burner, each 30,000 BTU/hr
- Thermostat (250°F-550°F) controlled oven
- Welded frame structure for best stability
- Standby S/S pilot for easy start
- Legs standard, 5" heavy duty caster optional
- 12" x 12" cast iron grate
- Anti-clogging pilot cover under the grate
- A pull-out crumb tray with angled handle front
- U-Shape oven burner with 31,000 BTU/hr
- Thermal coupling safety valve for the oven
- Stainless steel oven door with good insulation
- Stainless steel handle for bottom oven
- Kick plate at the bottom for easy servicing
- 34" NPT rear gas connection
- One year limited parts and labor warranty
- ▶ ETL Certified
- ▶ ETL Sanitation
- ▶ NSF Compliant







## **WARRANTY**

Cookline products are backed by a 1 Year parts and labor limited manufacturer warranty. The unit itself and parts within are guaranteed against manufacturing defects for a period of 1 year. Glass, due to its fragile nature, is not included under warranty coverage. Always inspect your delivery for freight damage before you accept it. Freight damage will not be considered a manufacturing defect and should be refused or remedied through a claim with the carrier.



Project:	Quantity:
Model #:	Approval:

# **TECHNICAL DATA**

## **DIMENSIONS**

Exterior Dimensions	36"L x 32.6"D x 60"H
Oven Dimensions	26.6"L x 23.5"D x 13.9"H
Packaging Dimensions	41"L x 40"D x 44"H
Unit Weight	368 lb.
Shipping Weight	456 lb.

## COOKING

Numbers of Burners	6
Burner BTU	30,000
Burner Style	Grates
Numbers of Ovens	1
Numbers of Oven Racks	2
Oven BTU	31,000
Oven Style	Standard Oven
Max. Oven Temperature	550°F
Total BTU	211,000
Control Type	Manual
Gas Inlet Size	3/4"
Gas Type	Natural Gas

### **CONSTRUCTION**

Exterior Material	Stainless Steel
Frame Structure	Welded
Number of Legs	4
Kick Plate Access	Yes
Pull Out Tray	Yes
Back Riser Shelf	Yes
Removable Grates	Yes

# **DIAGRAM**

MODEL: CR36-6



