

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

U-GM-3 68" Three Glass Door Merchandiser Refrigerator with LED Lighting



FEATURES

- · Whited coated exterior
- · High efficiency with auto defrost
- Refrigeration system keeps food at safe temperatures
- · Self-closing doors
- · Pull out black handle
- · Adjustable heavy-duty PVC coated shelves
- · Electronic control system
- · Preinstalled heavy-duty casters with brakes
- · Removable installation board
- · Hydro-Carbon R290 refrigerant

This Unity commercial glass door merchandiser refrigerator is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- ETL Sanitation Listed
- Conforms to UL & NSF Standards



SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.



Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	67.32"W x 28.35"D x 81"H
Interior Dimensions	64.29"W x 21.46"D x 61.55"H
Packaging Dimensions	69.29"W x 32.28"D x 86.68"H
Net Volume	50 cu. ft.
Unit Weight	441 lb.
Shipping Weight	514 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	6.8
Watts	700W
Plug Type	NEMA 5-15P
Power Cord Length	84"

COOLING

Temperature Range	33°F to 50°F
Refrigerant	R290
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	1/2

CONSTRUCTION

Exterior Material	Painted Sheet
Exterior Color	White
Interior Material	Painted Sheet
Insulation Material	Foamed-in-Place Polyurethane
Door Style	Swing
Door Type	Glass
Shelf Size	L/R: (10) 19.88"W x 21.73"D
	Middle: (10) 22.6"W x 21.73"D
Shelf Material	PVC Coated Steel
Adjustable Shelf	Yes
Interior Light	L.E.D
Mobility Wheels/Casters	(8) Qty: 4 with brakes, 4 without

TECHNICAL DRAWING

MODEL: U-GM-3

MFR ITEM: SS-P1500WA



3.2"



