# 24" DEEP BACK BAR COOLER



## EBB59-24

EUERIS

30 . .



## **EBB Series**

### **Refrigeration System**

• Side mounted, self-contained and fully detachable Blizzard R290 condensing unit uses environmentally friendly, EPA-compliant R290 refrigerant with zero (0) Ozone Depletion Potential (ODP) and three (3) Global Warming Potential (GWP). Blizzard R290 is easily replaceable and requires no on-site brazing.

· Electronically commutated (ECM) fan motors achieve rapid cooling with less energy consumption.

- $\cdot$  Full-length air duct ensures optimal cold air circulation.
- Time-initiated and temperature-terminated auto defrost cycle for seamless operation. • Large capacity, corrosion-resistant condenser and evaporator coils.

• Self-maintaining, energy-efficient condensate drain pan requires no external drains or electric heaters.

· High performance, auto-reverse condenser fan motor supports compressor ventilation and condenser coil cleaning.

· Pre-wired and ready to plug, 115V/60Hz/1Ph, NEMA 5-15P.

#### **Cabinet Construction**

- · Heavy duty stainless steel countertop with textured laminate, black vinyl exterior.
- $\cdot$  Open spaced interior with no walls between compartments.
- · Galvanized steel interior walls and high quality stainless steel floor.
- $\cdot 13/4$ " thick high density polyurethane insulation.
- · Built-in caster thread receptacles.

### Lighting

· Shielded LED bar lighting with on/off switch provides bright, high color illumination at lower heat output.

#### Doors

· Textured laminate, black vinyl exterior with galvanized steel interior.

- $\cdot 13/4$ " thick high density polyurethane insulation.
- · Snap-in magnetic door gasket make cleaning and replacement an easy process.
- · High strength, recessed door handles.
- · Pre-installed door locks keep your items safe from theft.
- · Two epoxy coated, steel wire shelves per section.
- · Height adjustable stainless steel clips.
- · Multi-function digital controller with easy to read LED display.
- · Factory preset temperature, 35°F.
- Temperature setting range from 33°F to 54°F.
- · Audible overheat protection alarm for compressor and condenser coil.

### Options

- · Additional shelving.
- $\cdot$  3" or 5" swivel casters with locks.
- · 3.5" 6" height-adjustable and interchangeable legs.



Туре	Doors	Capacity Cu. Ft.	12 oz. Cans	12 oz. Bottles	Shelves	Refrigerant	HP	Power V-Hz-Ph	Amps	Crated Weight	Exterior Dimensions		
											L	D	H*
REF	2	17	560	357	4	R-290	1/4+	115-60-1	3.5	274 lbs	57.75"	24.5"	37.25"

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). (↑) Product capacity is calculated based on standard industry figures. (\*) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.

VER. 8/18/2023



· High streng · Pre-installe Shelving

# 24" DEEP BACK BAR COOLER



# **EBB Series**

## **DIMENSIONAL DATA**

EBB59-24

	L	57.75 in.		
External Dims.	D	24.5 in.		
	H*	37.25 in.		
Crated Weight		274 lbs.		
Doors/Drawers/I	ids	2		
Max Weight Sup	oort	-		
STORAGE DAT	Α			
Net Capacity Cu.	Ft. 🏲	17		
Shelves		4		
Barrels		_		
20 oz. Bottles		-		
12 oz. Bottles		357		
12 oz. Cans		560		
8" Mugs		-		
# of Pans (Top)		-		
# of Pans (Drawe	er)	-		
Dividers		-		
Trays		_		

## **ELECTRICAL DATA**


Voltage	115-60-1
Full Load Amperage	3.5A
Feed Wires w/ Ground	3
Cord Length	9ft
NEMA Plug Type	(•1) NEMA 5-15P


### **REFRIGERATION DATA**

Compressor	Side
Refrigerant	R-290
Compressor HP	1/4+
BTU/HR <sup>†</sup>	1926


### KEY

D L FD SD GD	Lic Ho Fu So	oor 1 11 Door 11 Door 11 Door 11 Door ass Door	R REF F FRZ DUAL DR	Refrige Refrige Freezer Freezer REF/FRZ Drawer	)	
		Elevation	Right	Plan	3D	Back
KC	C					






FRONT



SIDE



**PLAN VIEW** 

AIRFLOW

## **ACCESSORIES & OPTIONS**

Additional Shelving
AJL03-00

- CASA3-01
- CASA5-01
- Contact Everest Refrigeration for more information.
- Interchangeable Leg for Caster (Optional)
- 3" Overall Height Caster Assembly (2) Front (2) Rear
- 5" Overall Height Caster Assembly (2) Front (2) Rear

(†)Based on evaporating temperature of 23°F (-5°C) & condensing temperature of 131°F (55°C). ( ) Product capacity is calculated based on standard industry figures. (\*) Reference plan view for clarification on caster/unit height. If dimensions and capacity are critical, please contact Everest Refrigeration. Blizzard R290 replacement is at the sole discretion of Everest Refrigeration. Specifications subject to change without notice.

VER. 8/18/2023