

Long Beach, CA 90808 Tel. 310-900-1000 Fax. 310-900-1077 www.turboairinc.com

| Project: | | |
|-------------------|--------|------|
| Model #: | | |
| Item #: | | |
| Available W/H: | | Qty: |
| Approval: | | |
| AIA #: | SIS #: | |
| CSI Section 11400 | | |
| | | |

Chef Base Refrigerator

Patented Self-Cleaning Condenser



Chef Bases Super Deluxe Series

Model : TCBE-82SDR-N



____ FEATURES & BENEFITS ____

Self-Cleaning Condenser

The accumulation of dust in the condenser can cause the failure or breakdown of refrigerators. Refrigerators run normally until they reach a certain level of accumulation. At some point, when they are over the limit, their performance drops quickly resulting in damage to, or disposal of the stored products inside. The Self-Cleaning Condenser device keeps the condenser clean and prevents system failure by automatically brushing daily.

Hydrocarbon refrigerants (R-290)

With innovative and eco-friendly technology, Turbo Air brings you hydrocarbon refrigerators designed to meet DOE's Energy Conservation Standards in 2017 and to use EPA's SNAP Program approved HC refrigerants. Hydrocarbon refrigerants do not deplete the ozone layer and have very low contribution to global warming (ODP-0, GWP-3).

Strong body and durable construction Built with heavy duty 16 ga. stainless steel, Chef Base top is manufactured of one-piece reinforced stainless steel to ensure durability.

- Digital temperature display on front panel
- Each left side drawer accommodates up to 6" deep three (3) full size pans and right side drawer accommodates up to 6" deep two (2) full size pans (drawer pans not included)

Top is insulated to eliminate heat transfer to the interior of cabinet

Countertops

TCBE-36SDR-N6/48/52SDR-N supports up to 788 pounds of equipment. TCBE-72/82SDR-N supports up to 1,192 pounds of equipment. TCBE-96SDR-N supports up to 1,435 pounds of equipment.

Durable stainless steel drawers

Side mount compressor unit

Compressors positioned on the side of the units makes servicing our units easy. Our front air intake feature also allows this model to be highly efficient in narrow spaces.

- High-density polyurethane insulation The entire cabinet structure and solid doors are foamed-in-place using high density, CFC free polyurethane insulation.
- Refrigerator holds 33°F ~ 38°F for the best in food preservation



| Mode TCBE-82S | | Drawers | CU./FT. 16.04 | Capacity (lbs.) | НР 1/3 | AMPS 6.2 | Weight (lbs.) | (inches) 835/8 x 32 x 201/4 |
|---------------|---|---------|------------------|-------------------|-----------|----------|---------------|--------------------------------|
| Mala | 1 | D | | Countertop Weight | UD | | Crated | $L x D^* x H^{\dagger}$ |

Ver.20230612 Printed in U.S.A.

* Depth does not include 1" for rear spacers. † Height does not include 5" for caster height.

Chef Base Refrigerator

Model : TCBE-82SDR-N

| ELECTRICAL DATA | | | | |
|--|-------------------|--|--|--|
| Voltage | 115/60/1 | | | |
| Plug Type | NEMA 5-15P | | | |
| Full Load Amperes | 6.2 | | | |
| Compressor HP | 1/3 | | | |
| Cord Length (ft.) | 9 | | | |
| Refrigerant | R-290 | | | |
| DIMENSIONAL DATA | | | | |
| Ext. Length Overall (in.) | 835/8 (2123mm) | | | |
| Ext. Depth Overall (in.)* | 32 (815mm) | | | |
| Ext. Height Overall (in.) [†] | 201/4 (513mm) | | | |
| # of Drawers | 4 | | | |
| Net Capacity (cu. ft.) | 16.04 | | | |
| Net Weight (lbs.) | 412 | | | |
| Gross Weight (lbs.) | 469 | | | |

Design and specifications subject to change without notice.

Actual shipping weight may differ due to extra packing materials for product protection. * Depth does not include 1" for rear spacers.

Height does not include 5" for caster height.

• WARRANTY : 5 Year Parts and Labor Warranty 7 Year Compressor Warranty

STANDARD FEATURES

- Anti-corrosion coated evaporator
- Self-contained system
- 4" dia. swivel casters


OPTIONAL ACCESSORIES

• 6" stainless steel leg: 30221M0600


PLAN VIEW


(unit : inch)

* Each drawer accommodates up to 6" deep full size pans (drawer pans not included)



TOP VIEW





Ver.20230612

Turbo Air : 800-627-0032
 GK : 800-500-3519
 Warranty : 800-381-7770
 AC : 888-900-1002

7 YEAR WARRANTY

Intertek

NATURAL Refrigerant

